

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
TAXA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN, OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - II" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL GAS WELL OTHER

1. Name of Operator
Vernon E. Faulconer

2. Address of Operator
1100 Peoples National Bank, Tyler, TX 75702

3. Location of Well
UNIT LETTER G 2310 FEET FROM THE East LINE AND 1820 FEET FROM
THE North LINE, SECTION 6 TOWNSHIP 17-S RANGE 38-E N.M.P.M.

4. Field and Pool, or Wildcat
West Garrett (Devonian)

7. Unit Agreement Name
N/A

8. Farm or Lease Name
Mattie Price

9. Well No.
6

10. Field and Pool, or Wildcat
West Garrett (Devonian)

11. Elevation (Show whether DF, RT, GR, etc.)

12. County
Lea

10. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Laid down tubing, perforated 10,550-51' and 10,010-011'. Squeezed with 115 sacks cement. Perforated 7120-21' and 6600-01', Squeezed 115 sacks cement. Perforated 6854-74', acidized, tested salt water. Squeezed perforations 6854-74' with 115 sacks cement, drilled out cement, tested casing and perforation to 1000#, everything held. Perforated 10,290-296'; 10,272-78'; 10,262-270'. Acidized perforations with 1000 gals. acid, swabbed salt water with show of oil. Shut down operation. 2 7/8" set at 10,081' with Guiberson Unipac V1 packer.

Intent is to convert well at a later date to SWDW.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Don R. Genter TITLE Controller DATE April 30, 1980

APPROVED BY Jerry Sexton TITLE Dir. E. Supv. DATE MAY 5 1980

CONDITIONS OF APPROVAL, IF ANY:

El Paso 5/5/81

m