

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-8712	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator AZTEC OIL & GAS COMPANY	8. Farm or Lease Name STATE "NV"
3. Address of Operator P. O. BOX 837, HOBBS, NEW MEXICO 88240	9. Well No. 2
4. Location of Well UNIT LETTER <u>H</u> , <u>1852</u> FEET FROM THE <u>North</u> LINE AND <u>554</u> FEET FROM THE <u>East</u> LINE, SECTION <u>28</u> TOWNSHIP <u>17-S</u> RANGE <u>34-E</u> NMPM.	10. Field and Pool or Wildcat UNDESIGNATED
15. Elevation (Show whether DF, RT, GR, etc.) 4064 DF	12. County LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" Hole to 9000'. Set New 5 1/2", 15 & 17#, N-80 Casing at 9000'. Cemented with 1400 Sxs Hilliburton Light Weight and 300 Sxs Class C Cement. Plug down at 2:00 P.M. 9-3-71.

Ran Temperature Survey after 8 hrs, Found top cement at 2990' PBTD 8954'.

Pressured Casing to 3000 psi for 30 minutes. Held Okay.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED original signed by
LESTER L. DUKE TITLE DISTRICT SUPERINTENDENT DATE 9-13-71

APPROVED BY Joe D. Ramsey TITLE Dist. I, Sup. DATE SEP 14 1971

CONDITIONS OF APPROVAL, IF ANY:

of large
small 41 not
●●●●●

RECEIVED

SEP 13 1971

OIL CONSERVATION COMM.
HOBBS, N. M.