

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.

B-1520

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Mobil Oil Corporation	8. Form or Lease Name Bridges State
3. Address of Operator Box 633, Midland, Texas 79701	9. Well No. 167
4. Location of Well UNIT LETTER O 1980 FEET FROM THE East LINE AND 660 FEET FROM THE South LINE, SECTION 22 TOWNSHIP 17-S RANGE 34-E N.M.P.M.	10. Field and Pool, or Wildcat Vac Grayburg - S.A.
11. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Treat the San Andres Perfs. (4690-4706) (16'OA-20 Holes) w/1000 gals. of the following cleanout solution:
A. 800 gals. of Xylene Bottoms
B. 200 gals. of 15% Regular, HCL Acid
C. 2 gals. of Adofoam (10 gals. of Adofoam/1000 gals of acid)
Acidize the San Andres Perfs. (4690-4706) (16'OA-20 Holes) with 5000 gals. of 15%, Non-Emulsion, Iron stabilized, HCL Acid. Run 2" Salta PVC Lined Injection tubing and an Injection Packer. Load the tubing-casing annulus with fresh water treated with 10 gals. of cortron 2207/1000 gals. of water. Set the packer at approximately 4640'

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine O. Tucker TITLE Proration Clerk DATE 1-22-74

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: