

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
K5458	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry hole		7. Unit Agreement Name
2. Name of Operator Coquina Oil Corporation		8. Farm or Lease Name Durham State
3. Address of Operator 418 Bldg. of the Southwest, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER <u>H</u> <u>1980</u> FEET FROM THE <u>N</u> LINE AND <u>660</u> FEET FROM THE <u>E</u> LINE, SECTION <u>11</u> TOWNSHIP <u>17-S</u> RANGE <u>36-E</u> N.M.P.M.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) GL 3822 KB 3833		12. County Lea

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 6-26-72 Spotted 30 sx. Class H cement in bottom of 4 1/2" casing. Top cement at 3863'.
- 6-27-72 Loaded 4 1/2" casing with mud. Cut 4 1/2" casing with chemical cutter at 3250'. Pulled and laid down 101 jts. 3253' of 4 1/2" casing.
- 6-28-72 Ran tubing. Loaded hole with mud. Spotted 30 sx. Class H cement 3131-3251. Spotted 30 sx. Class H cement 2943-3063'. Spotted 40 sacks Class H cement across bottom of 8 5/8" from 260'-360'.
- 6-29-72 Spotted 10 sx. Class H cement in top of 8 5/8" from 0-10'. Installed swage and valve on top 8 5/8". Erected DHM. P&A complete 6-29-72.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>J.B. Taylor</u>	TITLE <u>Superintendent</u>	DATE <u>6-30-72</u>
APPROVED BY <u>Nathan E. Clegg</u>	TITLE <u>Oil Engineer</u>	DATE <u>6-30-72</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

JUL 3 1972

OIL CONSERVATION COMM.  
FEDERAL

JUL 3 1972