

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. 62005 PROP DEPTH 4300' TYPE RT
DATE

F.R. 12-6-71; Opr's Elev. 3822' GL, 3833' DF
PD 4300' RL (Queen)
Contractor- Cactus
1-3-72 TD 4045'; WOC
Gored 3976-4002'; rec 22½' sd, anhy & anhydritic
sd, bldg oil in sd
DST 3970-4040', open 1 hr, rec 1380' GCM, 30 min
1-10-72 ISIP 2044#, FP 1080-1584#, 1 hr FSI# 2016#
2-7-72 TD 4045'; "Tight"
3-13-72 TD 4045'; "Tight"
TD 4045'; Tstg
Perf 3984-96' w/ 2 SPF
Acid (3984-96') 1500' gals
Flwd gas @ TSTM (3984-96')
Frac (3984-96') 19,000 gals + 14,000# sd

LEA

Undesignated

NM Sec 11, T17S, R36E

COQUINA OIL CORP.

#1 Durham - State

Page #2

3-20-72	TD 4045'; Tstg "Tight"
6-12-72	TD 4045'; Tstg "Tight"
6-19-72	TD 4045'; Prep P&A
	Flwd @ 80 MCFGPD (3984-96')
6-26-72	TD 4045'; Prep P&A
7-10-72	TD 4045'; PLUGGED & ABANDONED
	LOG TOPS: Anhydrite 1914', Yates 3048', Queen 3955'
7-15-72	COMPLETION REPORTED