

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B-3385

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Gulf Oil Corporation	8. Farm or Lease Name Ritts-State
3. Address of Operator Box 670, Hobbs, New Mexico 88240	9. Well No. 2
4. Location of Well UNIT LETTER <u>H</u> <u>2080</u> FEET FROM THE <u>North</u> LINE AND <u>560</u> FEET FROM THE <u>East</u> LINE, SECTION <u>21</u> TOWNSHIP <u>17-S</u> RANGE <u>34-E</u> NMPM.	10. Field and Pool, or Vildcat Undes North Vacuum Abo
15. Elevation (Show whether DF, RT, GR, etc.) 4058' GIL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 1 joint, 31' of 13-4/8" OD 48# casing with Rat hole machine on January 25, 1972. Cemented to surface with ready mix.

McVay Drilling Company spudded 12-1/4" hole at 9:00 AM, January 27, 1972. Drilled to 1627'. Ran 49 joints, 1607' of 8-5/8" OD 24# K-55 ST&C casing set and cemented at 1623' with 620 sacks of Class C with 4% gel and 200 sacks of Class C with 2% Ca Cl2. Cement circulated. WOC and NU 18 hours. Tested casing with 1500#, 30 minutes, OK.

Started drilling 7-7/8" hole at 1627' at 6:15 PM, January 29, 1972.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Glyn Stone TITLE Petroleum Engineer DATE January 31, 1972

APPROVED BY John W. Runyan TITLE Geologist DATE FEB 1 1972

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JAN 31 1972

OIL CONSERVATION COMM.
HOBBs, N. M.