- DISTRIBU		NEW MEXICO	NEW MEXICO OIL CONSERVATION COMMISSION				Form C-103 Superacies Old C-102 and C-103 Effective 1-1-65	
U.S.G.S. LAND OFFICE						State X  5. State OII 6 Go	Fee	
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  1. OIL TO GAB TO GAB.						7, Unit Agreement Name		
SHELL OIL COMPANY						E. Farm or Lease Name		
. Address of Ore		ON, TX 77001				State K 9. Well No.		
4. Location of We		980 FEET FROM THE	south	198	30 FLET FROM	10, Field and Pool	ol, or Wildcat	
eas		19 TOWNSHIP						
		15. Elevation (Sho 3994	-	RT, GR, etc.)		12. County Lea		
í é.	Check Ap	propriate Box To Ind ENTION TO:	dicate Natu	re of Notice,	-	ner Data REPORT OF:		
PERFORM REMEDIA TEMPORARILY ABAY PULL OR ALTER CA.	IDON	PLUG AND ABA Change Plans	C 601	MEDIAL WORK  MENCE DRILLING  ING TEST AND CEN  OTHER SQUEEZ	ENT JOS		NG CASING ND ABANDOHMENT	
i7. Describe Frogramork) SEE RU 5-13-80:		tions (Clearly state all pen		-	_	-		
5-14-80:	RU & swabbed w	ell down & releat 08600'.	sedtl	og anchor &	pld 2 7/8'			
5-15-80:	hole w/brine wtr.							
5-16-80:	rate of 5 BPM @600 psi. Got & pumped 150 st 150 sx Class C displaced 6 bb pump for 5 mine @1500 psi. Af held @1400 psi	er @1890'. Pressed 400 psi. Mixed cmt returns to a Class-C w/8% go cmt w/3% CaCl2 of the Class w/wtr @1 BPM (utes & ppd 2 bblster 10 minutes promined off.	& pumped surface. elled cmt cmt @2 1/2@1000 psi.s @1200 psppd 1/2 bbl	d tbg to 3 600 sx Cla Closed bra @2 1/2 BPM BPM @1200 After 6 i. After @1500 psi of cmt ret	ss C w/8% g denhead val @1200 psi. psi. With barrels dis 10 minutes w/pump shu ainer & rev	elled cmt @5 ve & mixed Mixed & pp cmt mixed placed shut ppd 1/2 bbls t off, press	down	
if. I hereby certify						_		
YY.H	STAR TOWN	A. J. FORE	LE SK. EI	NOK. IEUH.		DATE June 4	1, 1980	
CONDITIONS OF A	Josep Service			* -		aun	1 1AND	

17 e. 14 e.

- 5-17-80: WOC.
  - 18-80:
- 5-19-80: Ran 4 1/4" rock bit on 6 DCs on 2 7/8" tbg. Drld cmt from 1887'-1890'. Drld cmt retainer @1890'. Drld cmt from 1890'-1975'.
- 5-20-80: Finished drlg cmt from 1975-2080'. Circ'd hole clean. Tested squeezed perfs @2010' w/500 psi for 15 minutes held OK. Ran rock bit to 8585' & circ'd sand off RBP @8600'. POH & ran RBP retrieving head to 8600' & displaced hole w/2% KCl wtr. Latched onto RBP & POH.
- 5-21-80: Ran 2 7/8" x 31' bull plug mud anchor from 8734'-8765', 2 7/8" x 4' perforated sub from 8730-8734', 2 1/2" mechanical seating shoe from 8729' to 8730', 1 jt 2 7/8" tbg 8697-8729', Baker Model B tbg anchor from 8694-8697' on 280 jts 2 7/8" 8rd J55 tbg. RU Roland pump truck & ppd 1000 gals 15% acid @3 BPM @0 psi. Displaced w/20 bbls 2% KCl wtr @3 BPM @0 psi press. Removed BOP & landed tbg. Ran 2 1/2" x 1 1/2" RHBM 20' x 4' x 0 pump on 138 3/4", 108 7/8". 99 1" rods. Hung well on. RDPU.