

4-10-72 TD 4800'; PBD 4774'; Prep Sqz
Ppd 18 B salt wtr in 72 hrs (3931-40')
4-17-72 TD 4800'; PBD 4774'; Swbg
Sqzd (3931-40') 100 sx
Perf (San Andres) @ 4528', 4529', 4530', 4531',
4532', 4681', 4682', 4683', 4684', 4685', 4686',
4687', 4688', 4689', 4694-4700', 4703', 4704'
w/1 SPF
Acid (4528-4704') 500 gals
Swbd 4 BNO + 84 BFW in 11 hrs
4-24-72 TD 4800'; PBD 4774'; Ppg load
5-1-72 TD 4800'; PBD 4774'; TO Pmp
Ppd 31 BNO + 270 B salt wtr in 3 days (4528-4704')
5-8-72 TD 4800'; PBD 4774'; Swbg
Sqzd (4528-32') w/100 sx

5-8-72 Continued
Swbd 3 BLO + 44 B salt wtr in 11 hrs (4681-4704')
5-15-72 TD 4800'; PBD 4774'; TO Pmp
Ppd 27 BLO + 6 BNO + 312 BW in 72 hrs
5-22-72 TD 4800'; PBD 4774'; WO OCC Potential
Ppd 4 BO + 82 BW in 24 hrs, GOR TSTM,
Crav 34.6
5-30-72 TD 4800'; PBD 4774'; COMPLETE
LOG TOPS: Anhydrite 1645', Yates 2950',
Queen 3917', San Andres 4638'
6-3-72 COMPLETION REPORTED

COUNTY LEA FIELD VACUUM STATE NM 30-025-24038

OPR MOBIL OIL CORP. MAP
 174 Bridges - State
 Sec 15, T-17-S, R-34-E CO-ORD
 1980' FSL, 1780' PBL of Sec
 Spd 2-27-72 CLASS EL 40562
 Cmp 5-15-72

	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING				
8 5/8" at 365' w/450 sx				
5 1/2" at 4800' w/1550 sx				
LOGS EL GR RA IND HC A				

TD 4800'; PBD 4774'

IP (San Andres) Perfs 4681-4704' P 4 BOED + 82 BW. Pot based on
 24 hr test. GOR TSTM; Grav 34.6

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Cactus PROP DEPTH 4800' TYPE RT
 DATE

F.R. 2-15-72; Opr's Elev. 4044' CL
 PD 4800' RI (Grayburg-San Andres)
 Contractor - Cactus
 2-28-72 TD 365'; WOC
 3-6-72 Drlg. 4275' in
 3-13-72 TD 4800'; MORT
 Cored 4673-4723', rec 50', no descr
 3-20-72 TD 4800'; PBD 4774'; SIPHF
 Perf (Queen) 3931-40' w/1 SPF
 Acid (3931-40') 3000 gals
 Swbd Dry (3931-40')
 3-27-72 TD 4800'; PBD 4774'; Ppg load
 4-3-72 TD 4800'; PBD 4774'; Ppg load
 Ppd 1 BW in 24 hrs