ENERGY AND MINERALS	DEPARTMENT	
ws. er torice accord	JL CONSERVATION DIVISIO	
DISTRIBUTION	P. O. BOX 2088	Form C-103 ·
SANTA FE	SANTA FE, NEW MEXICO 87501	Revised 10-1-
FILE.	· · · · · · · · · · · · · · · · · · ·	5a. Indicate Type of Lease
U.S.O.S.		State X For
OPERATOR		5. State Oil & Gas Leitse No.
		B-4118
	SUMPRY MOTICES AND DEPORTS ON WELLS	mminimm
(DO NOT USE THIS	SUNDRY NOTICES AND REPORTS ON WELLS. FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. SE "APPLICATION FOR PERMIT =" (FORM C-1011 FOR SUCH PROPOSALS.)	
1. 01L X 6A	OTHER-	7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Phillips Petr	oleum Company	Lea
J. Address of Operator		9. Well No.
Room 401, 400	l Penbrook St., Odessa, Texas 79762	26
4. Location of Well		10. Field and Pool, or Wildcat
N	2180 FEET FROM THE WEST LINE AND 660 FEET FROM	
UNIT LETTER	FEET FROM THE LINE AND FEET FROM	Vacadiii, NOI EII ADO
South	LINE, SECTION 21 TOWNSHIP 17-S RANGE 34-E NMPM.	
. THE	LINE, SECTION TOWNSHIP RANGE HMPM.	
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	4063' GR	Lea
. 7777777777777777777777777777777777777		
NOT		REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CABING	CHANGE PLANS CASING TEST AND CEMENT JOB	1
	OTHER Perforate casing	and squeeze cmt
ОТНЕЯ	per OCD request	
17. Describe Proposed or C work) SEE RULE 1103	Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any propose
6-2-80	MI WS Unit. Pulled rods and tbg. Set BP at 3250', dum	ped 3 sxs sand on plug.
6-3-80		
	Perfd 5-1/2" csg w/4 holes at 1725'. Set E-Z Drill ret sxs Class "C" cmt w/2% CaCl ₂ . Flshd w/6 BW. Cmt circd in formation, reversed 3 sxs. WOC 17 hrs.	to surf. Sqzd 23 sxs
6-4-80	Drld ret at 1598' and cmt to 1656'.	
6-5-80	Finished drlg cmt to 1730'. Press perfs at 1725', would not hold. Set E-Z Drill ret at 1598'. Cmtd $w/250$ sxs Cl "C" cmt. Flshd $w/5-1/2$ bbls wtr. Cmt circd. Pulled out of ret and reversed out 5 sxs.	
6-7-80	Drld cmt ret from 1598-1600'.	
6/8-9/80	Dwn 48 hrscrew off.	
6-10-80	Drld out cmt to 1725'. Tested perf in 5-1/2" csg to 10 plug at 3527'. Pulled tbg, DC's, and bit. Ran 2-3/8" tool. Unseat BP. Pulled tbg and BP.	00#, OK. Washed over tbg w/BP retrieving

Set 286 jts of 2-3/8" tbg and anchor at 8841'. Ran rods and 2" x 1-1/4" x 20' pmp set at 8840'. MO WS Unit.

Sr. Engineering Specialist

June 11, 1980

...J<u>UN 1 6 1980</u>

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

W. J. Mueller

6-11-80

skm

Orig Signed hy

PEROVED BY

Dist 1, Supt.

CONDITIONS OF APPROVAL, IF ANYI