

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.

B-2073

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Phillips Petroleum Company	8. Farm or Lease Name Santa Fe
3. Address of Operator Room 711, Phillips Bldg., Odessa, Texas 79761	9. Well No. 122
4. Location of Well UNIT LETTER H , 1800 FEET FROM THE north LINE AND 760 FEET FROM THE east LINE, SECTION 19 TOWNSHIP 17-S RANGE 35-E N.M.P.M.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) GR 3980'	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER **set production casing string** ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole f/1750' to 9000'. Reached total depth 7:30 PM, 5-9-72. Cond hole and mud. Schlumberger ran SW-Neutron, GR-caliper and laterolog. Cond hole and mud. 5-11-72: Set 267 jts. 5-1/2" csg at 8997' bottom to top as follows: 52 jts (1700') 17#, K-55, ST&C ACond 64 jts (2200') 15.5#, K-55, ST&C ACond 84 jts (2900') 14#, K-55, ST&C ACond 52 jts (1700') 15.5#, K-55, ST&C ACond 15 jts (497') 17#, K-55, ST&C ACond

BJ cemented w/1800 ax Trinity LW followed by 250 ax Class H cement. Plug to 8963' bumped w/2000#. WOC 18 hrs., tested csg w/2000# for 30 minutes, ok. Ran temperature survey, TOC at 2950! (Released rig at 11 PM, 5-11-72.)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED  **W. J. Mueller** TITLE **Senior Reservoir Engineer**

DATE **5-18-72**

Orig. Signed by
Joe D. Ramey
Dist. I. Supv.

APPROVED BY _____ TITLE _____

DATE **MAY 22 1972**

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAY 19 1972

OIL CONSERVATION COMM.
HOBBS, N. M.

STG 11-1