

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ **DRY HOLE**

2. NAME OF OPERATOR
Amoco Production Company

3. ADDRESS OF OPERATOR
BOX 68, HOBBS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1830' FSL x 660' FWL Sec. 26 (Unit L, NW/4 SW/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)
3605' R.D.B.

5. LEASE DESIGNATION AND SERIAL NO.
NM-030941

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
BATE FEDERAL

9. WELL NO.
2

10. FIELD AND POOL, OR WILDCAT
EAST GEM YATES

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
26-19-33 NMPM

12. COUNTY OR PARISH
LEA

13. STATE
N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETION ☐
ABANDON* ☒
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers, and zones pertinent to this work.)*

On 4-18-72, 4 1/2" OD 9.5" K-55 Casing liner was set from 3188' to 3453' (TD) and cemented w/ 40Sx. Incon + 50# Tuf Plug + 104. 4el 7 flakes. Reversed 18Sx. WOC 24 hrs. Test 1000# OK Perf 3427-3431 w/ 2LSPF. Acid 500 gal 15% MCA. + 1000 gal 15% LSTNE. Swab Dry. Deepened from 3453 to 3456 Swab 40 BLW + 175 BNW 7 hrs. No show of Oil or Gas.

Dry Hole

Propose to P+ A as follows: Spot 25 x Incon salt sat. Cement plug across perfs. (3427-3431) shoot and pull 7" casing from approx 2900'. Spot 600 Sx Incon salt saturated cement plug 2935-1300. Spot 10 Sx salt sat. cement plug @ surface & erect P+ A marker. Make final cleanup and restage ground to contour (all intervals w/ heavy mud laden fluid)

18. I hereby certify that the foregoing is true and correct

SIGNED

AREA SUPERINTENDENT

TITLE

DATE

4-27-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

APR 28 1972

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

4- USGS- H
1- Div
1- SUSP
1- RRY

RECEIVED

MAY 2 1972

OIL CONSERVATION COMM.
HOBBS, N. M.