

63cc Shipp #3

F 11-17-37

DST #1 5285-5327, (3/4" bttm hole chk, tool opened @ 4 A.M., wk blo air inc to fair blo air/15"), Op 15", SI 60", Op 90", SI 180", No GTS, No GIDP. Rec 20' OCW, 527' SOCW, 270' sulf wtr. Chlorides 2850 ppm drlg wtr, T/rec 5,700 ppm, B/rec 26,600 ppm. FP 114-379, SIP 1948-1879, HP 2285-2264, BHT 98°. MFE Rec. 31,240 ppm.

DST #2 5546-5667 (3/4" bttm hole choke), Op 15", SI 60", Op 40", SI 80", No GTS, No GIDP. Rec 3485' drlg wtr & 820' sul wtr. Chlorides T/rec 2375 ppm, M/rec 1900 ppm, B/rec 2240 ppm, Pit 2850 ppm. FP 1669-1902, SIP 1902-1924, HP 2456-2435. MFE Rec 1900 cc sul wtr.

DST #3 8882-9184, Op 20", SI 120", Op 100", SI 200". Rec. 795' drlg mud, 315' Sli GCM, 90' Sli O&GCM & 90' HO&GCM. HP 4364-4364, SEP 1368-1595, FP 229-287 & 488-517. MFE Rec 1.72 cu ft @ 200 psi (2600 cc) 1250 cc oil & 1350 cc HO&GCM. API 34.8 @ 60°, 70% gas, 20% mud, 10% oil. BHT 140°.

DST #4 11,498-11,640, Op 20", SI 90", Op 30", SI 60", Very wk bl, died/15". Rec. 1500' wtr cushion, 15' drlg mud. HP 5347-5347, FP 732-732, SIP 1074-846. MFE Rec 1250 cc drlg mud, 18 psi, BHT 160°.

RECEIVED

JUL 10 1972

OIL CONSERVATION COMM.
HOUSTON, TEXAS