

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.
--

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name --
2. Name of Operator Pubco Petroleum Corporation	8. Farm or Lease Name Shipp
3. Address of Operator P. O. Box 869, Albuquerque, New Mexico 87103	9. Well No. 3
4. Location of Well UNIT LETTER <u>F</u> <u>2130</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM <u>West</u> LINE, SECTION <u>11</u> TOWNSHIP <u>17S</u> RANGE <u>37E</u> HMPM.	10. Field and Pool, or Wildcat Unnamed
15. Elevation (Show whether DF, RT, GR, etc.) 3744.9' GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 124 joints (4797.45') 9-5/8" 36# K-55 casing. Set @ 4800'. Cement with 375 sacks Dowell lightweight and 300 sacks Class "C", 2% CaCl. Cement circulated. P.D. @ 7:45 P.M. 6/11/72. Used thread lock on bottom 3 joints. Tack-welded in 4 quadrants on bottom two collars. Top of cement 2740'.

WOC 18 hours. Pressure tested both blind rams and pipe rams to 1000 psi for 30 minutes. Drilled 50' cement & plug. Held okay.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles W. Sanders TITLE Area Production Manager DATE 6/13/72

APPROVED BY Joe D. Ramey TITLE Dist. I, Supv. DATE JUN 22 1972

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 21 1972

OIL CONSERVATION COMM.
HOBBS, N. M.

Oil Conservation Comm.
Hobbs, N.M. 88401
June 21, 1972

Mr. [illegible]