

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Pubco Petroleum Corporation		5. State Oil & Gas Lease No. --
3. Address of Operator P. O. Box 869, Albuquerque, New Mexico		7. Unit Agreement Name --
4. Location of Well UNIT LETTER <u>L</u> <u>1874</u> FEET FROM THE <u>South</u> LINE AND <u>554</u> FEET FROM THE <u>West</u> LINE, SECTION <u>11</u> TOWNSHIP <u>17S</u> RANGE <u>37E</u> NMPM.		8. Farm or Lease Name Shipp
15. Elevation (Show whether DF, RT, GR, etc.) 3748 GL		9. Well No. <u>4</u>
		10. Field and Pool, or Wildcat Humble City Strawn
		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded @ 7 A.M. 2/02/73. Ran 11 joints (427') 13-3/8" 48# casing. Landed @ 420'. Cemented with 350 sacks Class "C", 2% CaCl₂. Cement circulated. P.D. @ 12:30 P.M. 2/03/73. Tack-welded collars in four quadrants on bottom two joints. Use thread lock on bottom 3 joints. WOC 12 hours. Tested BOP and casing to 600 psi for 30 minutes before drilling out.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. C. Johnson Title Vice President Production DATE 2/05/73
Original Signed by Joe D. Raney
Dist. I, Supv.
APPROVED BY _____ TITLE _____ DATE FEB 9 1973
CONDITIONS OF APPROVAL, IF ANY: