

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
K-5385-1	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Read & Stevens, Inc.		Amerada - State
3. Address of Operator		9. Well No.
P. O. Box 2126, Roswell, New Mexico 88201		1
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>N</u> , <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM		Lovington Queen
THE <u>West</u> LINE, SECTION <u>14</u> TOWNSHIP <u>17-S</u> RANGE <u>36-E</u> NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3834' GR		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 3:45 P.M., 3-5-73, drilled 11" hole to 325'. Ran 8 joints, 324.4' of 8 5/8", 24#, J-55 casing, set at 323' RKB. Cemented with 350 sx. Class C cement with 2% CaCl₂. Plug down at 10:00 P.M., 3-5-73. Circulated 25 sx. cement. WOC for 18 hrs. Pressure tested to 500# for 30 min., held ok.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Carl A. Schellinger</u>	TITLE <u>Agent</u>	DATE <u>3-6-73</u>
Orig. Signed by <u>Joe D. Ramsey</u>		
APPROVED BY <u>Joe D. Ramsey</u>	TITLE <u>Agent</u>	DATE <u>3-6-73</u>
CONDITIONS OF APPROVAL, IF ANY:		