

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMI.

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> X OTHER- Dry	7. Unit Agreement Name
2. Name of Operator Texas International Petroleum Corporation	8. Farm or Lease Name Nicholson
3. Address of Operator 1720 Wilco Building, Midland, Texas 79701	9. Well No. 3
4. Location of Well UNIT LETTER N 2086 FEET FROM THE West LINE AND 554 FEET FROM THE South LINE, SECTION 10 TOWNSHIP 17 S RANGE 37 E NMPM.	10. Field and Pool, or Wildcat Humble City (Strawn)
15. Elevation (Show whether DF, RT, GR, etc.) 3747.8 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to 11,866' on 1-16-74. Spotted 100' (45 sx) Class H cement plug from TD-11766'. Spotted 100' (45 sx) Class H cement plug 10,940' - 10,840'. Spotted 585' (240 sx) Class H cement plug 9,675' - 9,090'. Dressed off plug to 9,300'. Spotted 100' (35 sx) Class H cement plug 6,870' - 6,770'. Spotted 100' (35 sx) Class H cement plug 4,525' - 4,425' (half in and half out of 8-5/8" intermediate casing shoe). Pulled 1,200' 8-5/8" casing. Spotted 100' (67 sx) Class H cement plug 1,240' - 1,140' (half in and half out of 8-5/8" stub). Spotted 100' (70 sx) Class H cement plug 465' - 365' (half in and half out of 12-3/4" surface casing shoe). Dumped 10 sx Class H plug in surface pipe at surface 1-20-74.

Welded dry hole marker to surface pipe.

Pits will be filled and location levelled when conditions permit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED D. C. Helms TITLE Division Engineer DATE 1-21-74
APPROVED BY John W. Runyan TITLE Geologist DATE 1-21-74
CONDITIONS OF APPROVAL, IF ANY: