

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLI
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0481695

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Walton Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 17, 19-S, 33-E

12. COUNTY OR PARISH 13. STATE

Lea New Mexico

1. OIL WELL GAS WELL OTHER Dry hole

2. NAME OF OPERATOR
Gulf Oil Corporation

3. ADDRESS OF OPERATOR
Box 670, Hobbs, New Mexico 8824 0

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 330' FWL, Section 17, 19-S, 33-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3636' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other) Plug and Abandon

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plans have been made to plug and abandon as follows: Spot 50 sack Class C neat cement plug No. 1 from 3220' to 3320', 60 sack cement plug No. 2 from 2900' to 3000', 60 sack cement plug No. 3 from 1350' to 1450', 50 sack cement plug No. 4 from 200' to 300' and 20 sack cement plug No. 5 from 50' to surface. Install dry hole marker and clean location.

AMENDMENT: Approved subject to possible future requirement that well and road area be ripped and relevelled.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. J. Breazeale

TITLE Area Engineer

DATE January 8, 1974

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
JAN 10 1974

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side