

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy 2200
T. Salt
B. Salt 3400
T. Yates 3450
T. 7 Rivers
T. Queen 4400
T. Grayburg
T. San Andres 5350
T. Glorita 6925
T. Paddock
T. Blinbry
T. Tubb
T. Drinkard
T. Abo
T. Wolfcamp 9900
T. Penn. 10725
T. Cisco (Bough C)

T. Canyon
T. Strawn 11400
T. Atoka 11614
T. Miss
T. Devonian
T. Silurian
T. Montoya
T. Simpson
T. McKee
T. Ellenburger
T. Gr. Wash
T. Granite
T. Delaware Sand
T. Bone Springs
T.
T.
T.

Northwestern New Mexico

T. Ojo Alamo
T. Kirtland-Fruitland
T. Pictured Cliffs
T. Cliff House
T. Menefee
T. Point Lookout
T. Mancos
T. Gallup
Base Greenhorn
T. Dakota
T. Morrison
T. Todilto
T. Entrada
T. Wingate
T. Chinle
T. Permian
T. Penn. "A"

T. Penn. "B"
T. Penn. "C"
T. Penn. "D"
T. Leadville
T. Madison
T. Elbert
T. McCracken
T. Ignacio Qtzte
T. Granite
T.
T.
T.
T.
T.
T.
T.
T.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	2200	2200	Shale & sand				
2200	3250	1050	Sand & Salt - Anhy				
3250	3500	150	Salt & Anhy				
3400	4400	1000	Yates				
4400	5350	950	Queen				
5350	6925	1575	San Andres				
6925	9000	2075	Glorita				
9000	9900	900	Yaso				
9900	10725	825	Wolfcamp				
10725	11400	675	Penn.				
11400	11600	200	Strawn				
11614	11710	96	Atoka				