

COPIES RECEIVED	
TRIBUTION	
FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-6673	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Penroc Oil Corporation		8. Farm or Lease Name Humble City-State
3. Address of Operator P. O. Drawer 831, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER <u>C</u> <u>2086</u> FEET FROM THE <u>West</u> LINE AND <u>766</u> FEET FROM THE <u>North</u> LINE, SECTION <u>15</u> TOWNSHIP <u>17 S</u> RANGE <u>37 E</u> NMPN.		10. Field and Pool, or Wildcat Unders. Humble City Strawn
15. Elevation (Show whether DF, RT, GR, etc.) 3761' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10/18/74: Spudded @ 11:00 A.M.
10/19/74: Drilled 17 1/2" hole to 429'. Ran 429' 13 3/8" 48# casing, cemented w/450 sacks Class "C" cement w/2% Calcium Chloride. Plug down at 9:15 P.M. Cement circulated. Tested casing in 18 hrs to 800#, held O.K.
10/28/74: Drilled 11" hole to 4700'. Ran 4700' 32# & 48# casing. Cemented w/350 sacks Howco-Lite and 300 sacks Class "C" cement w/2% Calcium Chloride. Plug down 9:15 A.M. Tested casing in 18 hrs to 1200#, held O.K. Top cement @ 3390'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED M. Roberts TITLE Prod. Superintendent DATE 10/31/74

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: