

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATE	
FILE	
U.S.G.C.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDARY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR NOTICES TO WELLS IN DIFFERENT RESERVOIRS. USE APPLICATION FOR REPORT ON PRODUCTION FOR OTHER RESERVOIRS.)

1. Name of Operator
Gulf Oil Corporation

2. Address of Operator
Box 670, Hobbs, New Mexico 88240

3. Location of Well
UNIT LETTER **F** **1650** FEET FROM THE **North** LINE AND **1650** FEET FROM THE **West** LINE, SECTION **10** TOWNSHIP **19-S** RANGE **34-E** COUNTY

4. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
E-7824

6. Unit Agreement Name

7. Term of Lease Name
Lea ED State (NCT-B)

8. Well No.
1

9. Field and Pool, or Wildcat
Undesignated

10. Elevation (Show whether BF, RT, CR, etc.)
3922' GL

11. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPER. ☐	PLUG AND ABANDONMENT ☐
FULL OR ALTHR CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	
		OTHER ☐	

Plugged and Abandoned

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEC RULE 1103.

12,689' TD, 12,336' PB.

Pulled tubing and packer. Set CI BP at 11,300'. Loaded hole with abandonment mud. Cap BP with 20 sacks of Class H cement to 11,151'. Cut and recovered 7-5/8" casing from 6783'. Loaded hole with abandonment mud. Spotted 78 sack, 100' Class H cement plug from 6833' to 6733', across 7-5/8" stub at 6783'; 156 sack, 250' Class H cement plug from 6150' to 5900', across Delaware; 181 sack, 100' Class H cement plug from 3425' to 3325', across base of salt at 3380'; 269 sack, 300' Class H cement plug from 1950' to 1650', across top of salt at 1910' and 10-3/4" casing shoe at 1833'. Spotted 24 sack Class A cement plug from 50' to surface. Installed dry hole marker. Plugged and abandoned July 26, 1976. Will advise when location is ready for your final inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

19. SIGNATURE *D. F. Berlin* TITLE Area Engineer DATE July 26, 1976

20. APPROVED BY *John W. Runyan* TITLE _____ DATE _____

21. CONDITIONS OF APPROVAL, IF ANY

RECEIVED

JUL 27 1976

U.S. CONSERVATION COMM.
HOBBES, H. M.