

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REPERFORATE OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - \*\* (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator  
**Gulf Oil Corporation**

3. Address of Operator  
**Box 670, Hobbs, New Mexico 88240**

4. Location of Well  
UNIT LETTER **F**, **1650** FEET FROM THE **North** LINE AND **1650** FEET FROM  
THE **West** LINE, SECTION **10** TOWNSHIP **19-S** RANGE **34-E** N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)  
**3922' GL**

5a. Indicate Type of Lease  
State ☒ Fee ☐

5. State Oil & Gas Lease No.  
**E-7824**

7. Unit Agreement Name

8. Farm or Lease Name  
**Lea ED State (NCT-B)**

9. Well No.  
**1**

10. Field and Pool, or Wildcat  
**Undes La Rica Morrow**

12. County  
**Lea**

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

<b>NOTICE OF INTENTION TO:</b>		<b>SUBSEQUENT REPORT OF:</b>	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Reached total depth of 9-1/2" hole at 10,978' at 8:30 AM, April 23, 1976. Ran 157 joints and 1 cut joint, 6535' of 7-5/8" OD 29.70#, N-80 LT&C, 19 joints, 781' of 7-5/8" OD 26.40# S-95 LT&C and 86 joints, 3635' of 7-5/8" OD 26.40# N-80 LT&C casing. Total of 162 joints and 1 cut joint, 10,951'. Set and cemented at 10,978' with 1000 sacks of Class H cement containing .5% CFR-2. WOC 8 hours. TS indicated top of cement at 6830'. WOC over 18 hours. Tested casing with 4,000#, 30 minutes, OK.

Started drilling 6-1/2" hole at 10,978' on April 27, 1976.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED **D.F. Berlin** TITLE **Area Engineer** DATE **April 27, 1976**

APPROVED BY **Orig. Signed by Jerry Sutton** TITLE **Jerry Sutton** DATE **APR 20 1976**

CONDITIONS OF APPROVAL, IF ANY