NO. OF COPIES RECEIVED		
DISTRIBUTION		Form C-103 Supersedes Old
SANTAFE	NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103
FILE		Effective 1-1-65
U.S.G.S.		5a. Indicate Type of Lecse
LAND OFFICE	_	State X
OPERATOR		5. State Oil & Gas Lease No.
CLIVE		B-1553
(DO NOT USE THIS FORM FOR P	DRY NOTICES AND REPORTS ON WELLS PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. ATION FOR PERMIT -" (FORM C-1C1) FOR SUCH PROPOSALS.)	
1.	ATION FOR PERMIT -** (FORM C-101) FOR SUCH PROPOSALS.)	
OIL X GAS WELL	OTHER.	7. Unit Agreement Name
2. Name of Operator		0 5
Nich PLTE (LIU)	Claration and Tich	8, Farm or Lease Name State "4"
3. Address of Operator		9. Well No.
900 Building of the	Bouthwest, Midland, Texas 79701	3. Well 140.
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER	300 FEET FROM THE LINE AND FEET FR	Wildcat
THEUINE, SECT	TIONTOWNSHIPRANGENMP	
		** (///////////////////////////////////
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	3877.4 GR	I ca
Check	Appropriate Box To Indicate Nature of Notice, Report or C	Other Deep
NOTICE OF		NT REPORT OF:
	308320021	NI REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	A 750 to 0 1 1 1
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	ALTERING CASING
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	PLUG AND ABANOCHAB
	OTHER	ompletion operations 📉 🔀
OTHER		
17. Describe Proposed or Completed	Descritions (Clearly state all posting of the	
1/28/75 Spudded well	Operations (Clearly state all pertinent details, and give pertinent dates, including	ng estimated date of starting any proposed
•	1:15 A. M. Ren 12-3/4" C. D. 36# cag. to 398	5'. Circ. 75 sx. 100 23
nrs. resten	to 300 psi for 30 min. 20 psi pressure apop.	Coch Will
2/21/75 Ran 8-5/811 C	. J. 24# csg. 3 32# csg. to 5lod'. Cemented w.	/2700 ss. Circ. 100 sx.
WCC 60 hrs.	rested to 2,000 psi for 30 min., 50 psi pressur	re arop.
3/15/75 Reached I. I). of 8750'. Ran logs.	
3/16/75 Set cement pl	ugs from 8750' to \$500' and 5475' to 5275'.	
3/17/75 Ran 4-1/2" (. D. csg. liner from 4869' to 6298'. Cemented w	v/350 xx. xc/ full cost
Reversed out	25 sx. WCC 504 hrs. Tested to 1000 psi for 30	min 35 not not you de-
4/9/75 Peri'd. w/l s	hot per ft. from 6091' to 6240' (selected). Acidiz	inition, or par pressure dro
· · · · · · · · · · · · · · · · · · ·	tom hole pump and rods. Kan 2-3/8" (.). tubir	rea w/4000 gais. 18-30 ac
4/24/75 Set pumpting u	om note pump and rous. Ash 2-3/3" C. D. Moll	ig, set at b223'.
	•	
5/8/75 Startea pumpi		
7/7/75 Well pumping	4 SO and 36 BW per day.	
8.1 hereby certify that the information	above is true and complete to the best of my knowledge and belief.	
10 -2 -4	·	
IGNED W DWA	Vice President	DATE July 9, 1975
) v v v v v v v v v v v v v v v v v v v	DATE
	Controls	
PPROVED BY Oil &	Gas Insp.	العام المعالمة المساورين

CONDITIONS OF APPROVAL, IF ANY: