NO. OF COPIES RECEIVES		
DISTRIBUTION		Form C-103 Supersedes Old
···	MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103
FILE	MENICO OIL GOINGEN TOTAL GOINGGOIGH	Effective 1-1-85
U.S.G.S.		5a. Indicate Type of Lease
LAND OFFICE	•	State Fea X
OPERATOR		5. State Oil & Gas Lease No.
SUNDRY NOTICES A	ND REPORTS ON WELLS	
1. OIL GAS OTHER-	* (FORM C-101) FOR SUCH PROPOSALS.)	7. Unit Agreement Name
2. Name of Operator		8. Form or Lease Name
Jake L. Hamon		Fannye M. Holloway
3. Address of Operator		9. Well No.
611 Petroleum Bldg., Mic	iland, Texas 79701	3
4. Location of Well WHIT LETTER G 1980? PERT P.	North LINE AND 19801 FEET FR	10. Field and Pool, or Wildest South Knowles Devoniar
THE East LINE, SECTION 13	TOWNSHIP 17 - S RANGE 38 - E	
11111111111111111111111111111111111111	evation (Show whether DF, RT, GR, etc.)	12. County
368/	6.7' Gr. 3704' K.B.	Lea
Check Appropriate B	ox To Indicate Nature of Notice, Report or (Other Data
NOTICE OF INTENTION TO	SUBSEQUE	NT REPORT OF:
PERFORM REMEDIAL WORK	PLUS AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANGOR	COMMENCE DRILLING OPHS.	PLUS AND ABANDONMENT
PULL OR ALTER CASING	HANGE PLANS CASING TEST AND CEMENT JOB X	
	OTHER	
STHER		
17. Describe Proposed or Completed Operations (Clearly work) SEE RULE 1 103.	state all pertinent details, and give pertinent dates, include	ng estimated date of starting any proposed
1. Spudded at 3:30 P. M. 8-24-75	j .	
2. Drilled 17-1/2" hole to 320'		
	from bottom to top:	
 Drilled 17-1/2" hole to 320' Ran 13-3/8" casing as follows 	from bottom to top: 5 S-80 23.13' 4 K-55 64.91'	
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68# 3 Jts 13-3/8", Buttress,	from bottom to top: 5 S-80 23.13' 6 K-55 64.91' 68#, K-55 110.83'	
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68#	from bottom to top: 5 S-80 23.13' 6 K-55 64.91' 68#, K-55 110.83'	
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68# 3 Jts 13-3/8", Buttress,	from bottom to top: 5-80 23.13' K-55 64.91' 68#, K-55 110.83' 72#, S-95 127.70'	
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68# 3 Jts 13-3/8", Buttress, 4 Jts 13-3/8", Buttress, 10 Jts Total on elevators 4. Casing set at 320' K.B. Ceme Plug Down at 3:15 A.M. 8-25-7	s from bottom to top: S-80 23.13' K-55 64.91' 68#, K-55 110.83' 72#, S-95 127.70' 326.57' ented with 325 sacks of Class C cement circulated to surface. 13-3/8" casing and BOP's to 1000 psi	•
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68# 3 Jts 13-3/8", Buttress, 4 Jts 13-3/8", Buttress, 10 Jts Total on elevators 4. Casing set at 320' K.B. Ceme Plug Down at 3:15 A.M. 8-25-7 5. WOC 24 hrs. Pressure tested	s from bottom to top: S-80 23.13' K-55 64.91' 68#, K-55 110.83' 72#, S-95 127.70' 326.57' ented with 325 sacks of Class C cement circulated to surface. 13-3/8" casing and BOP's to 1000 psi	•
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68# 3 Jts 13-3/8", Buttress, 4 Jts 13-3/8", Buttress, 10 Jts Total on elevators 4. Casing set at 320' K.B. Ceme Plug Down at 3:15 A.M. 8-25-7 5. WOC 24 hrs. Pressure tested	s from bottom to top: S-80 23.13' K-55 64.91' 68#, K-55 110.83' 72#, S-95 127.70' 326.57' ented with 325 sacks of Class C cement circulated to surface. 13-3/8" casing and BOP's to 1000 psi	•
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68# 3 Jts 13-3/8", Buttress, 4 Jts 13-3/8", Buttress, 10 Jts Total on elevators 4. Casing set at 320' K.B. Ceme Plug Down at 3:15 A.M. 8-25-7 5. WOC 24 hrs. Pressure tested	s from bottom to top: S-80 23.13' K-55 64.91' 68#, K-55 110.83' 72#, S-95 127.70' 326.57' ented with 325 sacks of Class C cement circulated to surface. 13-3/8" casing and BOP's to 1000 psi	•
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68# 3 Jts 13-3/8", Buttress, 4 Jts 13-3/8", Buttress, 10 Jts Total on elevators 4. Casing set at 320' K.B. Ceme Plug Down at 3:15 A.M. 8-25-7 5. WOC 24 hrs. Pressure tested	s from bottom to top: S-80 23.13' K-55 64.91' 68#, K-55 110.83' 72#, S-95 127.70' 326.57' ented with 325 sacks of Class C cement circulated to surface. 13-3/8" casing and BOP's to 1000 psi	•
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68# 3 Jts 13-3/8", Buttress, 4 Jts 13-3/8", Buttress, 10 Jts Total on elevators 4. Casing set at 320' K.B. Ceme Plug Down at 3:15 A.M. 8-25-7 5. WOC 24 hrs. Pressure tested pressure for 30 mins with no	from bottom to top: S-80 23.13' K-55 64.91' 68#, K-55 110.83' 72#, S-95 127.70' anted with 325 sacks of Class C cement circulated to surface. 13-3/8" casing and BOP's to 1000 psi pressure loss.	•
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68# 3 Jts 13-3/8", Buttress, 4 Jts 13-3/8", Buttress, 10 Jts Total on elevators 4. Casing set at 320' K.B. Ceme Plug Down at 3:15 A.M. 8-25-7 5. WOC 24 hrs. Pressure tested	from bottom to top: S-80 23.13' K-55 64.91' 68#, K-55 110.83' 72#, S-95 127.70' anted with 325 sacks of Class C cement circulated to surface. 13-3/8" casing and BOP's to 1000 psi pressure loss.	•
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68# 3 Jts 13-3/8", Buttress, 4 Jts 13-3/8", Buttress, 10 Jts Total on elevators 4. Casing set at 320' K.B. Ceme Plug Down at 3:15 A.M. 8-25-7 5. WOC 24 hrs. Pressure tested pressure for 30 mins with no	from bottom to top: S-80 23.13' K-55 64.91' 68#, K-55 110.83' 72#, S-95 127.70' 326.57' ented with 325 sacks of Class C cemer 75. Cement circulated to surface. 13-3/8" casing and BOP's to 1000 psi pressure loss.	. Held
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68# 3 Jts 13-3/8", Buttress, 4 Jts 13-3/8", Buttress, 10 Jts Total on elevators 4. Casing set at 320' K.B. Ceme Plug Down at 3:15 A.M. 8-25-7 5. WOC 24 hrs. Pressure tested pressure for 30 mins with no	from bottom to top: S-80 23.13' K-55 64.91' 68#, K-55 110.83' 72#, S-95 127.70' anted with 325 sacks of Class C cement circulated to surface. 13-3/8" casing and BOP's to 1000 psi pressure loss.	•
2. Drilled 17-1/2" hole to 320' 3. Ran 13-3/8" casing as follows 1 Jt 13-3/8", ST&C, 72# 2 Jts 13-3/8", ST&C, 68# 3 Jts 13-3/8", Buttress, 4 Jts 13-3/8", Buttress, 10 Jts Total on elevators 4. Casing set at 320' K.B. Ceme Plug Down at 3:15 A.M. 8-25-7 5. WOC 24 hrs. Pressure tested pressure for 30 mins with no	from bottom to top: S-80 23.13' K-55 64.91' 68#, K-55 110.83' 72#, S-95 127.70' 326.57' ented with 325 sacks of Class C cemer 75. Cement circulated to surface. 13-3/8" casing and BOP's to 1000 psi pressure loss.	. Held

· ·