

COPIES RECEIVED			
DISTRIBUTION			
SANTA FE			
FILE			
U.S.G.S.			
LAND OFFICE			
OPERATOR			

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-155-1	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		West Vacuum Unit
3. Address of Operator		8. Farm or Lease Name
P. O. Box 728 - Hobbs, New Mexico 88240		West Vacuum Unit
4. Location of Well		9. Well No.
UNIT LETTER <u>I</u> , <u>1360</u> FEET FROM THE <u>South</u> LINE AND <u>150</u> FEET FROM		10. Field and Pool, or Wildcat
THE <u>East</u> LINE, SECTION <u>33</u> TOWNSHIP <u>17-S</u> RANGE <u>34-E</u> NMPM.		Undesignated
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
4035' (GR)		Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TOTAL DEPTH 4800'

8-5/8" OD Casing Set @ 355'

1. Ran 4788' 5-1/2" OD casing and set @ 4800'.
2. Cemented w/25 sx. Class 'C' & followed w/800 sx TLW containing 4% gel, 5 lb. Gilsomite/sx & 10 lb. salt/sx. Followed w/200 sx Class 'C' Neat cement. Job complete 8:00 A.M., 11-29-75.
3. Test 5-1/2" OD csg w/1500# for 30 minutes 3:45-4:15 P.M. 12-1-75. Tested O.K.
4. Plug back total depth 4760'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Asst. District Supt. DATE 12-4-75

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

FEB 4 1975

U.S. CONSERVATION COMM.
HOBBS, N. M.