

COQUINA OIL CORPORATION
 Union State #1
 Drill Stem Tests

DST #1 8238'-8289' Bone Spring

| | | |
|-----------|-----------|-----------------|
| 15" PF | 63-63 psi | Wk blow thruout |
| 60" ISIP | 3095 psi | |
| 60" F | 84-84 psi | Wk blow thruout |
| 120" FSIP | 3095 psi | |

Rec: 5' drlg fluid out oil + 120' drlg fluid. Left bottom 4' of tool in hole. Prep to fish.

DST #2 9420'-9450' Bone Spring

| | | |
|-----------|-------------|------------------------------------|
| 15" PF | 84-105 psi | Fair blow thruout |
| 60" ISIP | 3386 psi | |
| 60" Flow | 127-169 psi | Fair blow thruout. GTS in 45" ISIM |
| 120" FSIP | 3033 psi | |
| Hyd | 4277 | |
| BHT | 110 | |

Rec.: 510' oil. Gr 34 @ 60 deg. + 150' salt water. 77,000 ppm (pit 12,000 ppm) + 30' drlg fluid.

DST #3 11,460'-11,476' Wolfcamp

| | | |
|-----------|-------------------|-----------|
| 15" PF | fair blow thruout | 42-42 psi |
| 60" ISIP | FAILED | |
| 60" F | Wk blow thruout | 42-42 psi |
| 120" FSIP | | 5947 psi |
| Hyd | | 5329 psi |
| Hyd | | 5329 psi |

Rec.: 9676' DPG + 210' oil (37 gravity @ 60 deg) + 40' DF.

DST #4 12,603'-12,655' Atoka Sd.

| <u>EVENT</u> | <u>BHP</u> | <u>REMARKS</u> |
|--------------|------------|----------------------|
| 15" Proflew | 35-105 | Very wk blow thruout |
| 60" ISIP | 5575 | |
| 60" F | 127-143 | Very wk blow thruout |
| 120" FSIP | 6058 | |
| Hyd | 6746-6704 | |
| BHT | 165 r | |