

COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Farnland International Energy Company		8. Farm or Lease Name Heeper
3. Address of Operator c/o Oil Reports & Gas Services, Inc., P.O. Box 763, Hobbs, New Mexico		9. Well No. 1
4. Location of Well UNIT LETTER B 660 FEET FROM THE North LINE AND 2080 FEET FROM THE East LINE, SECTION 27 TOWNSHIP 19 S RANGE 35 E NMPM.		10. Field and Pool, or Wildcat Undes. N. Pearl Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3722.5		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 8:30 AM 12/6/75. Cemented 13 3/8" 48# N-40 casing at 349 with 370 sacks class C 2% calcium chloride. Plug down 9:00 PM 12/6/75. Cement circulated. WOC 24 hours, test casing with 1000# for 30 minutes, O.K.

Cemented 9 5/8" 40# N-80 & K-55 Casing at 5000 with 1515 sacks Halliburton lite, 18% salt, 1/4# flocele & 3# Gilsenite per sack & 150 sacks class C 5% salt. Plug down 9:00 AM 12/24/75. Cement did not circulate. WOC 48 hours, test casing with 1500# for 30 minutes, test O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>Donna Walker</i></u>	TITLE Agent	DATE 1/23/76
APPROVED BY <u><i>Jerry Simon</i></u>	TITLE <u><i>Field A. Supv.</i></u>	DATE JAN 26 1976
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

JAN 23 1976

UCL CONSERVATION COMM.
HOBBS, R. M.