

SECONDEL SEE DECASE Second S	DISTRIBUTION		NEW MEXICO OIL CONSE	ON Form			
Under the Control of	SANTA FE FILE				·		
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK ** Type of Wein	U.S.G.S.						
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK **Type of Fig.** **Type of Fig.** **Type of Fig.** **Price of Fig.**				•	.5. St	ate Oil & Gas Lease No.	
DEFEND OR STATE OR ST	OPERATOR				777		
DELTA DELTA DELTA DELTA DELTA DELTA DELTA DELTA DELLA	APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK						
Suppose the state of the state	la. Type of Work				7. Ur	nit Agreement Name	
Texaco Inc. Addison of Special Properties Properti	b. Type of Well]	DEEPEN	PLUC	BACK A FO	rm or Lease Name	
The first of Species Tree of the Control of Species Tree of Sp		OCHER Wa	ter Injection	SINGLE X			
Above trace Casing: Coment first stage w/250 sx Halliburton Lite w/5#/sx clisonite & 8 %/ex salt followed by 500 sx class "C" cement with 8 %/sx salt followed by 500 sx class "C" cement w/18% salt. Above trace Describe Responded by 100 sx class accomplete to the test of my temporary and solvery approach of the last of my temporary and the last of my temporary a	2. Name of Operator			2016	9. We	9. Well No.	
P. O. Box 3109 Midland, Toxas 79702 Committee of Soil Decrease Decrease 134 Test report North Store	Texaco Inc.						
Surface Casing: 200 sx class "C" w/2% Cacl, 14.8#/gal=300% to circulate-cement must circulate. Surface Casing: 200 sx class "C" w/2% Cacl, 14.8#/gal=300% to circulate-cement must circulate. Surface Casing: 200 sx class "C" w/2% Cacl, 14.8#/gal=300% to circulate-cement must circulate. Surface Casing: 200 sx class "C" w/2% Cacl, 14.8#/gal=300% to circulate-cement must circulate. Surface Casing: 200 sx class "C" w/2% Cacl, 14.8#/gal=300% to circulate-cement must circulate. Surface Casing: 200 sx class "C" w/2% Cacl, 14.8#/gal=300% to circulate-cement must circulate. Surface Casing: 200 sx class "C" w/2% Cacl, 14.8#/gal=300% to circulate-cement must circulate. Surface Casing: Cement first stage w/250 sx Halliburton Lite 19/14/sx Gilsonite & 8#/sx sait followed by 500 sx class "C" cement with 8#/sx sait followed by 500 sx class "C" ceme		Midland	Tevas 70702		i i	·	
The state of the s				Ess seem the Nort	h was	VIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII	
LEVER PROPOSED CASING AND CEMENT FROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT FER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 11' 8 5/8" 248K-55 STC 350' 200 SX CIrculate 3. STEP OF HOLE SIZE OF CASING WEIGHT FER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 11' 7 7/8" 8 5/8" 248K-55 STC 350' 200 SX CIrculate Surface Casing: 200 SX class "C" N/2% Cacl, 14.8#/gal=300% to circulate-cement must circulate. Production Casing: Coment first stage N/250 SX Halliburton Lite W/5#/SX salt \$25 CF3-2: open DV tool \$2500' circulate 4-6 hrs. Second stage 1800 SX Halliburton Lite W/18% salt \$250 CF3-2: open DV tool \$2500' circulate 4-6 hrs. Second stage 1800 SX Halliburton Lite W/18% salt. ANOVE SPACE DESCRIPE, PROPOSED PROCRAMS IN PROPOSED NEW FOOD SX Class "C" cement W/18% salt. ANOVE SPACE DESCRIPE, PROPOSED PROCRAMS IN PROPOSED NEW FOOD SX Class "C" cement W/18% salt. ANOVE SPACE DESCRIPE, PROPOSED PROCRAMS IN PROPOSED NEW FOOD SX Class "C" cement W/18% salt. ANOVE SPACE DESCRIPE, PROPOSED PROCRAMS IN PROPOSED NEW FOOD SX Class "C" cement W/18% salt. DESCRIPTION OF A PROPOSED, PROCRAMS IN PROPOSED NEW FOOD SX Class "C" cement W/18% salt. ANOVE SPACE DESCRIPE, PROPOSED PROCRAMS IN PROPOSED NEW FOOD SX Class "C" cement W/18% salt. DESCRIPTION OF A PROPOSED, PROCRAMS IN PROPOSED NEW FOOD SX Class "C" cement W/18% salt. DESCRIPTION OF A PROPOSED, PROCRAMS IN PROPOSED NEW FOOD SX CLASS "C" cement W/18% salt. DESCRIPTION OF A PROPOSED, PROCRAMS IN PROPOSED NEW FOOD SX CLASS "C" cement W/18% salt. DESCRIPTION OF A PROPOSED NEW FOOD SX CLASS "C" CEMENT INCOME. THE ASSISTANT DIV. Petr. Engr. foot Street Stage Process Stor Food SX CLASS "C" CEMENT IN PROPOSED NEW FOOD SX CLASS "C" CEMENT IN PROPOSED NEW FOOD SX CLASS "C" CEMENT IN PROPOSED NEW FOOD SX CLASS "C" CEMENT WITH THE COME FOOD SX CLASS "C" C" CEMENT WITH THE COME FOOD							
### ASSISTANT DIV. Petr. Engrature for the best of my back. State 2012 on the large market for the best of my backless for the best of my back	AND 2 GET FROM	THE West	LINE OF SEC. 3]	TWP. 17-S RGE. 3		County	
Superior State S					//////////////////////////////////////		
Standard Branch Standard St		HHHH					
Standard Branch Standard St							
Supplied of the state of Scalar Fig. 1904 PROPOSED CASING AND CEMENT FROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 11" 8 5/8" 24/8K-55 STC 350! 200 SX Climenlate 7 7/8" 1 1/2" 10.5#K-55STC 850! 2800! 2800 SX Climenlate 2800 SX SACKS OF CEMENT EST. TOP 11 10.5#K-55STC 850! 200 SX Climenlate 2800 SX SACKS OF CEMENT EST. TOP 11 10.5#K-55STC 850! 2800! 2800 SX Climenlate 2800 SX SACKS OF CEMENT EST. TOP 2800! 2800 SX Climenlate 2800 SX SACKS OF CEMENT EST. TOP 2800! 2800 SX Climenlate 2800 SX SACKS OF CEMENT EST. TOP 2800! 2800 SX Climenlate 2800 SX SACKS OF CEMENT EST. TOP 2800 SX Climenlate 2800 SX SACKS OF CEMENT EST. TOP 2800 SX Climenlate 28				<u> </u>		_	
SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 11" 8 5/8" 24%X-55 STC 350! 200 sx Circulate 7 7/8" 1 1/2" 10.5%X-55 STC 4800! 2800 sx Circulate 2800 sx Circulate 2800 sx Clarculate 2800		,RT, etc.) 21A.	Kind & Status Flug. Bond	21B. Drilling Contractor	22.	Approx. Date Work will start	
SIZE OF HOLE SIZE OF CASING WHIGHT PER PROT SETTING DEPTH SACKS OF CEMENT EST. TOP 11" 8 5/8" 24%K-55 STC 350' 200 sx Cinculate 7 7/8" 1 1/2" 10.5%K-55STC 2600! 2800 sx Cinculate Surface Casing: 200 sx class "C" w/2% Cacl, 14.8%/gal < 300% to circulate- cement must circulate. Production Casing: Cement first stage w/250 sx Halliburton Lite 9/5%/sx cilsonite & 8%/sx salt followed by 500 sx class "C" cement with 8%/sx salt & 1% CFR-2: open DV tool @ 2500' circulate 4-6 hrs. Second stage 1800 sx Halliburton Lite w/18% salt + 250 sx Class "C" cement w/18% salt. ABOVE SPACE DESCRIBE PROPOSED PROCESAN: If Proposed is To DEFFIN OF TWO MACH, SIVE DATA ON PRESENT PRODUCTIVE FORE AND PROPOSED HEN PROPOSED HENCH PROPOSED HE					1	1-25-77	
11" 8 5/8" 24/K-55 STC 350! 200 sx Circulate 7 7/8" 1/2" 10.5#K-55STC 4800! 2800 sx Circulate 2800 sx Class "C" w/2% Cacl, 14.8#/gal = 300% to circulate 2800 sx Class "C" cement with 8#/sx 31t & 2% CFR-2: open DV tool © 2500' circulate 4-6 hrs. Second stage 1800 sx Halliburton Lite w/18% salt + 250 sx Class "C" cement w/18% salt. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If PROPOSED, IS TO DESPIT OF FROM PLUS PACE, SIVE DATA ON PROSECUTIVE ZONE AND PROPOSED NEW PROFESSION CONTROL OF THE STATE	23.		PROPOSED CASING AN	D CEMENT PROGRAM			
11" 8 5/8" 24/K-55 STC 350! 200 sx Circulate 7 7/8" 1/2" 10.5#K-55STC 4800! 2800 sx Circulate 2800 sx Class "C" w/2% Cacl, 14.8#/gal = 300% to circulate 2800 sx Class "C" cement with 8#/sx 31t & 2% CFR-2: open DV tool © 2500' circulate 4-6 hrs. Second stage 1800 sx Halliburton Lite w/18% salt + 250 sx Class "C" cement w/18% salt. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If PROPOSED, IS TO DESPIT OF FROM PLUS PACE, SIVE DATA ON PROSECUTIVE ZONE AND PROPOSED NEW PROFESSION CONTROL OF THE STATE		SIZE OF CASI	NG WEIGHT PER FOOT	SETTING DEPT	H SACKS OF CEN	MENT EST. TOP	
Surface Casing: 200 sx class "C" w/2% Cacl, 14.8#/gal = 300% to circulate- cement must circulate. Production Casing: Cement first stage w/250 sx Halliburton Lite w/5#/sx Gilsonite & 8#/sx salt followed by 500 sx class "C" cement with 8#/sx salt & \$ CFR-2: open DV tool @ 2500' circulate \$ 6 hrs. Second stage 1800 sx Halliburton Lite w/18% salt + 250 sx Class "C" cement w/18% salt. ***Rever space Describe Processed Processed in the w/18% salt + 250 sx Class "C" cement w/18% salt. ***Rever space Describe Processed Processed in the work of the best of my Superiodice and belief. ***Total Assistant Div. Petr. Engrature 11-10-77 **The Assistant Div. Petr. Engrature 11-10-77 *			24#K-55 STC	350!		Circulate	
Production Casing: Cement first stage w/250 sx Halliburton Lite w/5#/sx Gilsonite & 88/sx salt followed by 500 sx class "C" cement with 88/sx salt followed by 500 sx class "C" cement with 88/sx salt & 250 sx class "C" cement with 88/sx salt & 250 sx Halliburton Lite w/18% salt + 250 sx Class "C" cement w/18% salt. ABOVE SPACE DESCRIBE PRODUCTION Lite w/18% salt + 250 sx Class "C" cement w/18% salt. ABOVE SPACE DESCRIBE PRODUCTION LITE W/18% salt + 250 sx Class "C" cement w/18% salt. ABOVE SPACE DESCRIBE PRODUCT PROGRAM: IF PROPOSAL IS TO PECPEN ON PLUS PACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PROCUCE OF SITE AND PROPOSED NEW PROCU	7 7/8"	4 1/2"	10.5#K-55ST	C 4800!	2800 sx	Circulate	
Peroved by Approval, 15 any: Control Vacuum Unit Control Nacuum Unit Control Nacu	1800 sx Hallibu	: open DV rton Lite	tool @ 2500' c: w/18% salt + 2	irculate 4-6 50 sx Class	hrs. Seco "C" cement	ond stage w/18% salt.	
DATE ONDITIONS OF APPROVAL, 15 ANY: Inotes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief. Date Surveyed 11-7-77 Registered Professional Engineer and/gr Land Surveyer B. L. Eiland Central Vacuum Unit	hereby certify that the information	on above is true and	complete to the best of my k	npwledge and belief.		***************************************	
notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my knowledge and belief. Date Surveyed 11-7-77 Registered Professional Engineer and/gr Land Surveyor W. L. Eiland Centificate No.	PPROVED BY	45/2	TITLE	OF BRIC	可 介 	N 9 1978	
Date Surveyed 11-7-77 Registered Professional Engineer and/or Land Surveyed 2. L. Eiland Central Vacuum Unit Certificate No.	ONDITIONS OF APPROVAL, IF	ANY:			. –		
Date Surveyed 11-7-77 Registered Professional Engineer and/or Land Surveyed 2. L. Eiland Central Vacuum Unit Certificate No.	A Carrie						
Date Surveyed 11-7-77 Registered Professional Engineer and/or Land Surveyed 2. L. Eiland Central Vacuum Unit Central Vacuum Unit Central Vacuum Unit	1		•	e service	notes of acti	ual surveys made by me or	
Central Vacuum Unit Central Vacuum Unit Certificate No.			 		is true and	correct to the best of my	
Central Vacuum Unit Central Vacuum Unit Certificate No.							
Central Vacuum Unit B. L. Eiland Certificate No.					Date Surveyed		
Central Vacuum Unit B. L. Eiland Certificate No.							
Gentral Vacuum Unit B. L. Eiland Certificate No.					1 1		
Central Vacuum Um Certificate No.					1165. %	Eduna	
Certificate No.		Central Va	acuum Unit	**************		lland	
100 100 100 1000 1000 2010 2010 2010 1000 1000 500 0 4386					© 4386		

.

2/1

9.







TEXACO, INC.

PRODUCING DEPARTMENT-U.S. (EAST)
MIDLAND, TEXAS



SCALE: NONE	DATE	EST. NO.	DRG. NO.
DRAWN BY JWD			
CHECKED BY RDW		ŀ	
APPROVED BY			

EXHIBIT "B"