

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised March 25, 1999

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

WELL API NO. 30-025-25724
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-1565
7. Lease Name or Unit Agreement Name: Central Vacuum Unit
8. Well No. 58
9. Pool name or Wildcat Vacuum Grayburg San Andres
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3999' GL

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
Oil Well ☐ Gas Well ☐ Other Injection ☒

2. Name of Operator  
Texaco Exploration & Production

3. Address of Operator  
15 Smith Road - Midland, Texas 79705

4. Well Location  
Unit Letter A : 1310 feet from the North line and 132 feet from the East line  
Section 36 Township 17S Range 34E NMPM County Lea

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: Squeeze holes in casing ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1. Set CIBP @ 4300'.
2. Circulate hole clean with fresh water.
3. Spot 50' (3 sacks) Class C Cement with 2% calcium chloride above CIBP 4300' to 4250'.
4. Pull up 2 jts; reverse circulate hole clean with fresh water.
5. Spot Brian/gel from 4250' to 3000'.
6. Spot (27.06 sacks) Class C Cement with 2% calcium chloride 3000' to 2600'.
7. Reverse circulate hole clean with fresh water.
8. Spot Brian/gel from 2600' to 1300'. Shut down.
9. Pump in right angle cement from 1300' to 1000' 75 sacks followed with 100 sacks of Class C Cement with 2% calcium chloride.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Laura Skinner TITLE Regulatory Specialist DATE 06-18-02

Type or print name Laura Skinner Telephone No. 915-687-7355

(This space for State use)

APPROVED BY  
Conditions of approval, if any:

ORIGINAL SIGNED BY  
GARY W. TITLER  
QC FIELD REPRESENTATIVE II/STAFF MANAGER

DATE 2 2 2002