



OIL CONSERVATION DIVISION

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-25730
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil / Gas Lease No.	B- 2146
7. Lease Name or Unit Agreement Name	CENTRAL VACUUM UNIT
8. Well No.	82
9. Pool Name or Wildcat	VACUUM GRAYBURG SAN ANDRES
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3394' GL	

SUNDRY NOTICES AND REPORTS ON WELL
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☐ GAS WELL ☐ OTHER WATER INJECTION

2. Name of Operator
TEXACO EXPLORATION & PRODUCTION INC.

3. Address of Operator
205 E. Bender, HOBBS, NM 88240

4. Well Location

Unit Letter K : 1333 Feet From The SOUTH Line and 2528 Feet From The WEST Line

Section 36 Township 17S Range 34E NMPM LEA COUNTY

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐
COMMENCE DRILLING OPERATION ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4/1/96 -4/5/96

1. MIRU, INSTALLED BOP, TOH W/ INJECTION TUBING & PKR. TAGGED FILL @ 4264' & CLEANED OUT TO 4790 (PBTD) & CIRCD CLEAN. RAN CASING INSPECTION/CEMENT BOND LOG FROM 4790'-3500'.
2. SET TREATING PKR @ 4314', TSTD CSG TO 500#, OK. ACIDIZED PERFS FROM 4340'-4719' W/ 5000 GALS 20% NEFE HCL, MAX P = 2305#, AIR = 5.1 BPM. SI 2 HRS.
3. TOH W/ PKR. TIH W/ 4 1/2" INJ PKR ON 137 JTS 2 3/8" DUO-LINE INJ TBG. CIRCD HOLE W/ PKR FLUID, SET INJECTION PKR @ 4224'. TSTD CSG TO 520 PSI FOR 30 MIN, HELD OK.
4. RETURNED WELL TO INJECTION.

(ORIGINAL CHART ATTACHED, COPY OF CHART ON BACK)

OPT 4-18-96 INJECTING 2042 BWPD @ 750 PSI

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Monte C. Duncan TITLE Engr Asst

DATE 5/6/96

TYPE OR PRINT NAME Monte C. Duncan

Telephone No. 397-0418

(This space for State Use)

APPROVED BY GARY WINK ORIGINAL SIGNED BY GARY WINK TITLE FIELD REP. II

CONDITIONS OF APPROVAL, IF ANY:

DATE MAY 09 1996