

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-101
Revised 1-1-65

5A. Indicate Type of Lease	
STATE <input type="checkbox"/>	FEE <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work		7. Unit Agreement Name	
b. Type of Well		8. Farm or Lease Name	
DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/>		Scharb Com	
OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		9. Well No.	
SINGLE ZONE <input checked="" type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>		1	
2. Name of Operator		10. Field and Pool, or Wildcat	
Read & Stevens, Inc.		Scharb Bone Spring	
3. Address of Operator		12. County	
P. O. Box 2126, Roswell, New Mexico 88201		Lea	
4. Location of Well		19. Proposed Depth	
UNIT LETTER J LOCATED 1980 FEET FROM THE South LINE		10,300'	
AND 1980 FEET FROM THE East LINE OF SEC. 7 TWP. 19-S RGE. 35-E NMPM		19A. Formation	
		Bore Spring	
		20. Rotary or C.T.	
		Rotary	
21. Elevations (Show whether DF, RT, etc.)		21B. Drilling Contractor	
3866.2'GR-3879' RKB		Rial Drilling Co.	
21A. Kind & Status Plug. Bond		22. Approx. Date Work will start	
Statewide		1-21-78	

23.

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17 1/2"	12 3/4"	34 #	400'	375 sx.	Circulated
11"	8 5/8"	32#	4000'	700 sx.	Circulated
7 7/8"	4 1/2"	10.5# & 11.6#	10,300'	200 sx.	

1. Drill 17 1/2" hole to 400' and run 12 3/4", 34#, S. T. & C. csg. to 400', cemented with 375 sx. Class C cement w/2% CaCl₂. Cement Circulated.
2. Drill 11" hole to 4000' and run 8 5/8", 32#, S. T. & C. csg. to 4000', cemented with 700 sx. Class H cement w/2% CaCl₂. Cement circulated.
3. Drill 7 7/8" hole to 10,300' and if production indicated, run 4 1/2", 10.5# & 11.6#, K-55 & N-80, S. T. & C. & L. T. & C. csg. to 10,300', cemented w/200 sx. Class C cement with 3/4 of 1% CFR-2 & 8# salt per sx.
4. Rial Drilling Company Rig No. 1 is a National 50 CA equipped with a 10" Series 900 Shaffer double hydraulic blow out preventer and a 10" Series 900 Hydril G-K with a Hydril 3 station BOP closing unit and a Hydril K-80 accumulator.
5. Gas is dedicated to Warren Pet. Co.

APPROVAL VALID
FOR 90 DAYS UNLESS
DRILLING COMMENCED,

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed John L. Anderson Jr. Title Agent Date January 17, 1978

(This space for State Use)

APPROVED BY Lucy S. S. S. TITLE SUPERVISOR DISTRICT I DATE JAN 22 1978

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JAN 19 1978

OIL CONSERVATION COMM.
HOBBS, N. M.