

DEM - CARLSBAD

RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other Water Flood Injection Well

2. Name of Operator

Wallen Production Company 24540 (915) 683-2600

3. Address and Telephone No.

P.O. Box 1960, Midland, TX 79702

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FSL & 990' FEL, Sec. 30, T19S, R33E

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 073240

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Wallen Tonto #7 11591

9. API Well No.

30-025-25897

10. Field and Pool, or Exploratory Area

7-Rivers Yates South

11. County or Parish, State

Lea County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐
- Notice of Intent
-
- ☐
- Subsequent Report
-
- ☐
- Final Abandonment Notice

Reenter a plugged well

TYPE OF ACTION

- ☐
- Abandonment
-
- ☐
- Recompletion
-
- ☐
- Plugging Back
-
- ☐
- Casing Repair
-
- ☐
- Altering Casing
-
- ☐
- Other

- ☐
- Change of Plans
-
- ☐
- New Construction
-
- ☐
- Non-Routine Fracturing
-
- ☐
- Water Shut-Off
-
- ☒
- Conversion to Injection
-
- ☐
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We will reenter well #7 and clean it out to TD (3123'). There is 7", 23#/ft., J-55 casing set to 2,930' and cemented to the surface of the ground and then we will place a Halliburton R-4, 7" X 2 7/8" plastic coated packer at 2,890' + with 2 7/8" glass tubing (tested to 2,500 PSI) and hook it to the well head, a 2 7/8" full opening plastic coated valve.

Subject to
Like Approval
by State

*APPROVED by O.C.D., Case No. 9736, Order No. R-9082, 14 Dec. 1989.

14. I hereby certify that the foregoing is true and correct

Signed Walter H. KingTitle EngineerDate 01-09-92

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date 2/12/92