

George R. Reddy

Consulting Geologist

Bus. (505) 623-6233

Res. (505) 623-3767

200 West First Street

Roswell, New Mexico 88201

Read & Stevens, Inc.
No. 1 UT State
660' FSL & 1980 FEL Sec. 2, T 19S, R 34E
Lea County, New Mexico

Core No. 2, 4992-5050
(Cut 58', Recovered 58')

- 4992-93 Dolo., gray, FX, Dns, N.S.
94 Anhy, gray, M-CX, Dns, N.S.
95 Sh, Dk gray, Dolo., N.S.
96 Sh, AA, interlamin w/Dolo, gray, VFX-FX, Dns, N.S.
97 Dolo, gray, VF-FX, Dns, N.S.
98 Dolo, gray, VFX, matrix w/scattered CX, Dns, N.S.
99 Dolo, tan, FX w/scattered CX Anhy., Dns, N.S.
5000 Dolo, gray-tan, VFX, Dns, N.S.
01 Dolo, AA, Argill., N.S.
02 Anhy, white-gray, CX, Dns, N.S.
03 Dolo, tan, Micro-VFX, Sandy, Dns, N.S.
04 SS, gray, FG, SA-R, Dolo. cmt., Tr Ø & Perm., N.S.
05 SS, AA but denser w/anhy. matrix, N.S.
06 SS, AA, cleaner, N.S.
07 SS, gray, FG, SR-R, well srted, Dolo. cmt., 70% light brown oil stain, Fluor.
08 SS, AA, show AA.
09 Dolo, gray, VFX, V/sandy, Dns, lamin, N.S.
10 Dolo, AA, N.S.
11 SS, lt gray, F-MG, SR, Dolo. cmt., sli fri, fair Ø & perm., N.S.
12 SS, lt. gray, FG, SA, Dolo cmt., tight, N.S.
13 SS, AA, N.S.
14 Dolo, gray, FX, sandy, Dns, N.S.
15 SS, lt. gray, F-MG, SA, lamin w/Blk Sh., N.S.
16 SS, AA, N.S.
17 SS, lt. gray, FG, SR-SA, well srted., sli dolo, fair Ø & perm., N.S.
18 SS, AA, lamin w/Blk sh, N.S.
19 SS & Sh AA, N.S.
20 Dolo, gray, F-MX, Sdy, Dns, N.S.
21 Dolo, AA, N.S.
22 Dolo, AA, N.S.
23 Dolo, incr. sdy, AA, N.S.
24 SS, gray, FG, A-SR, Dolo cmt, fairly clean w/trace Ø & perm., N.S.
25 SS, AA, lamin w/Sh, N.S.
26 SS, AA, w/Sh AA, N.S.
27 SS, AA, w/sh AA, N.S.
28 SS, AA, w/Sh AA, N.S.
29 SS, AA, N.S.
30 Dolo, gray, FX-MX, Dns, N.S.
31 Dolo, tan, VFX, Dns, N.S.

Read & Stevens, Inc.
No. 1 UT State
Core No. 2
Page 2

- 5031-5032 Dolo, AA, N.S.
5033 Dolo, AA, N.S.
5034 Shale, Dk Brn, silty, sli dolo., N.S.
5035 Dolo, gray & tan, F-Mx, Dns, lamin. w/Sh, Dk gray, N.S.
5036 SS, gray, F-MG, SA-A, Dolo, cmt., N.S.
5037 SS, AA, N.S.
5038 SS, AA, Anhy & Dolo matrix, tight, N.S.
5039 Dolo, tan & gray, VFX, lamin w/brn silty sh., N.S.
5040 Dolo, gray, FX, Dns, N.S.
5041 Dolo, tan, VFX, Dns, N.S.
5042 Dolo, gray, micro-x w/incl. of CG Anhy, Dns, N.S.
5043 Dolo, tan, VF-MX, Dns, N.S.
5044 Anhy, gray, CX, Dns, N.S.
5045 Anhy, whi, gray, F-CX, Dns, N.S.
5046 Anhy, AA, mixed w/Dolo, gray, VFX, Dns, N.S.
5047 Dolo, lt. gray, micro VFX, Dns, N.S.
5048 Dolo, tan, VFX, Dns, N.S.
5049 Dolo, gray, VFX, Dns, sdy, lamin w/Dk gray sh., N.S.
5050 Dolo, gray VF-FX, Dns, N.S.

CORING AND DRILLING RECORD
AMERICAN COLDSET CORPORATION
(505) 397-1407 (915) 683-1846
Hobbs, New Mexico 88240 Midland, Texas 79701

AREA: Hobbs NM.

DATE 8-16-16

1978

OPERATOR Record Software

OPERATOR REP. 161244

CONTRACTOR W.E.K. RIGS INC.

WELL NO. 1 LEASE UT

FIELD Quail St. S.S.

COUNTY LCP STATE N.M.

BIT SIZE	BIT NUMBER	CORE OR RUN NO	INTERVAL CORED/DRILLED	FEET CORED / DRILLED	FT REC'D	% REC'D	HOURS ON BOTTOM	FT/HR.			
OD	I.D.		FROM	TO							
7 1/2"	21/2"	14645	2	4992 - 5050	58	58	100%	29 1/2			
<hr/>											
MUD											
TYPE	VISC.	WT.	W/L	SAND	SOIL	GELS	GPM	AVERAGE WEIGHT	AVER R.P.M.	PRESSURE	
STARCH	31	111	18	1	-	-	210	160	1000	800	200

DEPTH	TIME	MIN PER FOOT	FORMATION / REMAR	DEPTH	TIME	MIN PER FOOT	FORMATION / REMAR
FROM.	TO	FROM	TO	FROM	TO	FROM	TO
4992	4993	1:00	11:30	30	8-16 AM		
				5023			
				24			
				25			
				26			
				27			
				28			
				29			
				30			
				31			
				32			
				33			
				34			
				35			
				36			
				37			
				38			
				39			
				40			
				41			
				42			
				43			
				44			
				45			
				46			
				47			
				48			
				49			
				50			
				51			
				52			
				53			
				54			
				55			
				56			
				57			
				58			
				59			
				60			
				61			
				62			

9' Pipe connection

COMMENTS:

ST. WT. 100,000

100,000 ft. 100,000 ft.

By J. E. R. Hobbs, NM