Form 9-331 (May 1963)	UNFIED STATES SUBMIT IN TRIPLICATE DEPARTMENT OF THE INTERIOR (Other instructions on response)			on re-l	Form approved. Budget Bureau No. 42-R1424. 5. LIASE DESIGNATION AND SERIAL NO.		
		GEOLOGICAL SURVEY			NM 16359		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)					6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
1. OIL GAS WELL XX OTHER					7. UNIT AGREEMENT NAME		
2. NAME OF OPERATOR					8. FARM OR LEASE NAME		
GULF OIL CORPORATION					Strange "A" Federal		
3. ADDRESS OF OPERATOR					9. WELL NO.		
P. O. Box 670, Hobbs, New Mexico 88240					1		
<ol> <li>LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface</li> </ol>					10. FIELD AND FOOL, OR WILDCAT Undesignated Quail Ridge Morrow		
1980' FSL & 660' FWL					11. SEC., T., R., M., OR BLK. AND BURVEY OR AREA Sec 15, T-19S, R-34E		
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, CR, etc.)			$\frac{5ec}{12. \text{ COUNTY OF PARISH}} \frac{13. \text{ STATE}}{13. \text{ STATE}}$		
		375	56' GL	I	ea	New Mexico	
16.	Check A	Appropriate Box To Indicate	Nature of Notice, Report	, or Other	Data	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
					ENT REFORT OF:		
TEST WATER SHU	-OFF	PULL OR ALTER CASING	WATER SHUT-OFF		REPAIRING V		
FRACTURE TREAT		MULTIPLE COMPLETE	FRACTURE TREATMENT		ALTERING CA		
SHOOT OR ACIDIZE		APANDON*	SHOOTING OR ACIDIZIN	G	ABANDONMEN		
REPAIR WELL		CHANGE PLANS	(Other) Ran & Ce	emented	ited Production Csg X		
(Other)	Completion or Recomp				of multiple completion on Well letion Report and Log form.)		
17. DESCRIBE PROPOSED proposed work, nent to this work		PERATIONS (Clearly state all perti- tionally drilled, give subsurface &	sent data D 1 to				

COPY TO O C S.

Reached TD (13,600') of 7-7/8" hole @ 10:00 P.M., 11-28-78. Ran 119 jts (4705.13') of 5-1/2" 17# S-95 LT&C and 223 jts & 1 cut jt (8867.37') of 5-1/2" 17# N-80 casing. Set @ 13,600' with float collar @ 13,518'. Cemented with 1585 sacks of Class "H" with 1% CFR-2 & .5% Halad 9. Plug down @ 12:30 P.M., 12-1-78. TSITOC @ 6000'. Wait on cement over 24 hours.

RECEIVED

DEC 20 1978

U. S. GEOLOGICAL SURVEY HOEBO MITH MEXICO

Tested 5-1/2" casing to 3000# for 30 minutes; held o.k.

. .

e an pick of a

