		COPY TO O	C. C.				
UNILD STATES  DEPARTMENT OF THE INTERIOR  GEOLOGICAL SURVEY				SUBMIT IN TRIPLICATION (Other instructions on reverse side)		Form approved. Budget Bureau No. 42-R1424.  5. LEASE DESIGNATION AND SERIAL NO.  NM 16359	
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)						6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
1.  OIL GAS XX OTHER						7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR						8. FARM OR LEASE NAME	
	L CORPORAT	Strange "A" Federal					
3. ADDRESS OF OPERATOR						9. WELL NO.	
P. O. Box 670, Hobbs, New Mexico 88240  4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*					1		
<ol> <li>LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*</li> <li>See also space 17 below.)</li> <li>At surface</li> </ol>					Undesignated  Quail Ridge Morrow		
					11. SEC., T., R., M.	OR BLK. AND	
1980' F	SL & 660'	FWL			SURVEY OR	AREA	
					Sec 15, 7	T-19S , R-34E ARISH   13. STATE	
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, R'					12. COUNTY OR PA	ARISH 13. STATE	
			3756' GL		Lea	New Mexico	
16.	Check Ap	propriate Box To Ind	icate Nature of Noti	ce, Report, or C	Other Data		
	TION TO:	1	SUBSEQUENT REPORT OF:				
TEST WATER SHUT-O	FF I	PULL OR ALTER CASING	WATER S	HUT OFF	7		
FRACTURE TREAT		AULTIPLE COMPLETE		TREATMENT	_	ING WELL.	
SHOOT OR ACIDIZE		ABANDON*		OR ACIDIZING	<del>-</del> i	ONMENT*	
REPAIR WELL		HANGE PLANS	(Other)	Set & Ceme	nted Interme	- [ ]	
(Other)	(37 cmm - 73					tion on Well	
nent to this work.)	• The state of the	RATIONS (Clearly state all nally drilled, give subsurf.  of 11" hole @	pertinent details, and gi ace locations and measur	ve pertinent dates, ed and true vertica	, including estimated at depths for all ma	I date of starting any trkers and zones perti-	
cut joir lst stag	t (5676') e with 500	of 8-5/8" 32# K ) sacks of HOWCO e with 1100 sack	<pre>&lt;-55 ST&amp;C 8 RT ) Lite &amp; 200 sa</pre>	casing. Se cks of Clas	t @ 5685'. s "C" Neat.	Cemented	

th cemented 2nd stage with 1100 sacks of cement with 1/4% Flocele & 18% salt followed by 200 sacks of Class "C" Neat. Plug down @ 11:30 A.M., 10-24-78. Cement circulated. Waited on cement over 24 hours.

Tested 8-5/8" 32# casing to 2000# for 30 minutes; held o.k.

Began drilling 7-7/8" hole @ 3:30 A.M., 10-26-78.

S. I hereby certify that the foregoing is frue and con	TITLE	Area Engineer	DECORD PLIE	10-26-78
(This space for Federal or State office use)  APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	Section 1	31 1978 (1) S	
	*See Instructio	ns on Reverse Side	NEW ME	