Read & Stevens, Inc. Quail State #3Y Sidewall Cores Page 2 Depth 1/2" Rec. SS, dk gry, brwnish gry, FG, soft, SA, dirty, 5189 lots of clay, N.S. NR 5188 1" Rec. SS, lt gry, VF-FG, SA-A, clean, well srtd, 5094 scat lt oil stain, scat fluor, fair cut Run 2 3/4" Rec. SS, gray, VF-FG, SA-SR, very clean, sli calc. 5193 N.S. NR 5192 NR 5190 1/2" Rec. SS, brnsh gry, VFG, SA, Dolo cmt, fairly clean, 5188늘 disintegrates in acid, N.S. 1/2" Rec. SS, gry, FG-MG clean, sli dolo cmt, disintegrates 5093 in acid, sli oil stain, good solid yel fluor, good cut w/chlorothane NR 5092 3/4" Rec. SS, gry, F-MG, SA-SR, clay, clean areas, Dolo 5070 cmt, N.S. 5069불 NR 3/4" Rec. SS, gry, FG, well srtd, sli Dolo cmt, good 5018 solid yel fluor, good cut 3/4" Rec. SS, gry, FG, well srtd, clean, sli Dolo cmt, 5007 disintegrates w/acid, good solid yel fluor, good cut 3/4" Rec. SS, AA, good solid yel fluor, good cut 5006 1/2" Rec. SS, AA, good fluor, good cut 1/2" Rec. SS, gry, F-MG, AA, sli Dolo cmt, very friable, 5005 5004 solid yel fluor, good cut 3/4" Rec. SS, red, VF-MG, dirty, silty, N.S. 4778 1" Rec. SS, very lt gry, VF-MG, Anhy cmt, patches of yel 4776

fluor, no stain, fair cut