

**UNIVERSITY PETROLEUM ENGINEERING, INC.**  
*Petroleum Reservoir Engineering*

DALLAS, TEXAS

PHILLIPS PETROLEUM CO.  
 E. VACUUM GRAYBURG S.A. UNIT 3229-005

DATE : 5-6-79  
 FORMATION : GRAYBURG

FULL DIAMETER ANALYSIS

FILE NO. : 3202-1118  
 ANALYSTS : NEFF

SAMPLE NUMBER	DEPTH	PERM. TO AIR (MD)	FOR. MAXIMUM 90 DEG	FLUID OIL	SATS. WTR	GRAIN DEN	DESCRIPTION	
							He	DOL
585	4777.0-78.0	2.5	1.0	7.6	15.6	33.0	2.86	DOL,SL/ANHY,SL/F,PP
586	4778.0-79.0	2.6	1.9	7.7	24.2	29.7	2.86	DOL,SL/ANHY,SL/F,PP
587	4779.0-80.0	1.0	0.8	6.3	25.9	26.9	2.87	DOL,SL/ANHY,SL/F,PP
588	4780.0-81.0	2.5	1.9	9.5	23.3	29.9	2.86	DOL,SL/ANHY,STY,PP
589	4781.0-82.0	1.1	4.2	7.7	23.0	28.6	2.87	DOL,SL/ANHY,STY,SL/F,PP
590	4782.0-83.0	1.8	1.4	6.4	23.7	25.0	2.87	DOL,SL/ANHY,PP,STY
591	4783.0-84.0	5.9	1.4	11.0	24.0	26.7	2.87	DOL,SL/ANHY,SL/F,PP,STY
592	4784.0-85.0	4.4	*	7.6	26.7	24.8	2.86	DOL,SL/ANHY,PP,STY

CORE NO. 14 4785.0-4845.0 CUT 60' REC 60'

593	4785.0-86.0	1.3	2.3	7.6	4.6	37.9	2.84	DOL,SL/ANHY,SL/F,SL/V
594	4786.0-87.0	1.7	4.6	2.5	11.4	55.6	2.84	DOL,SL/ANHY,SL/F,PP
595	4787.0-88.0	2.0	12.	10.6	22.2	27.8	2.86	DOL,SL/ANHY,SL/F,PP
596	4788.0-89.0	2.5	7.1	8.5	23.4	29.9	2.85	DOL,SL/ANHY,STY,SL/F
597	4789.0-90.0	2.7	1.1	8.4	16.3	31.6	2.87	DOL,SL/ANHY,PP,STY
598	4790.0-91.0	2.8	2.5	1.2	14.2	18.9	2.87	DOL,SL/ANHY,SL/V,SL/F
599	4791.0-92.0	4.5	3.9	5.9	14.5	41.0	2.88	DOL,SL/ANHY,STY,SL/V
600	4792.0-93.0	4.4	2.0	6.9	15.4	39.4	2.87	DOL,SL/ANHY,V/F,SL/V
601	4793.0-94.0	4.0	1.7	5.2	15.2	31.9	2.88	DOL,SL/ANHY,PP,STY
602	4794.0-95.0	6.9	5.9	6.3	15.9	33.3	2.88	DOL,SL/ANHY,PP,STY,SL/F
603	4795.0-96.0	6.2	5.6	7.4	20.7	28.6	2.87	DOL,SL/ANHY,PP,STY
604	4796.0-97.0	6.6	1.5	8.9	14.8	35.1	2.87	DOL,SL/ANHY,SL/U,SL/F,STY
605	4797.0-98.0	2.1	4.6	9.3	20.9	29.5	2.86	DOL,SL/ANHY,STY,SL/U
606	4798.0-99.0	4.5	4.2	6.5	22.8	28.6	2.88	DOL,SL/ANHY,STY,SL/U
607	4799.0-00.0	4.4	1.5	1.7	20.9	30.9	2.86	DOL,SL/ANHY,SL/V
608	4800.0-01.0	3.9	3.3	9.3	12.9	26.7	2.88	DOL,SL/ANHY,U
609	4801.0-02.0	2.7	2.3	8.7	13.9	26.4	2.87	DOL,SL/ANHY,SL/F,V,FOSS
610	4802.0-03.0	3.9	5.6	10.1	9.8	26.1	2.85	DOL,SL/ANHY,FOSS,V
611	4803.0-04.0	1.9	1.7	13.4	9.9	34.4	2.83	DOL,SL/ANHY,FOSS,V

These analyses, opinions or interpretations are based on observations and materials supplied by the client to whom, and for whose exclusive and confidential use, this report is made. The interpretations or opinions expressed represent the best judgment of Core Laboratories, Inc. (all errors and omissions excepted); but Core Laboratories, Inc. and its officers and employees, assume no responsibility and make no warranty or representations, as to the productivity, proper operations, or profitabilities of any oil, gas or other mineral well or sand in connection with which such report is used or relied upon.