

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

API No. 30-025-26230

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

B-1576

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO LIFTEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT - 11 FORM CHECKED FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Under East Vacuum Grayburg-San Andres Unit
2. Name of Operator Phillips Petroleum Company	8. Form of Lease Under East Vacuum Grayburg-San Andres Tract 3229
3. Address of Operator Room 401, 4001 Penbrook Street, Odessa, Texas 79762	9. Well No. 005
4. Location of Well UNIT LETTER M 1110 FEET FROM THE South LINE AND 1290 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 17-S RANGE 35-E NMPM.	10. Field and Pool or Well at Vacuum Grayburg/San Andres
15. Elevation (Show whether DE, RT, GR, etc.) 3965' GR	12. County Lea


16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:


PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 4-24-79 MI & RU Cactus Drlg. Spud w/17-1/2" hole drld 352'. Set 8 jts 13-3/8", 48#, H-40 ST&C csg set @ 352'. Howco cmt w/675 sxs Class H w/2% CaCl & 1/4#/sx Flocele in first 150 sxs. Disp plug to 326' w/51 bbls water. Circ 149 sxs cmt.
- 4-25-79 WIH w/12-1/4" bit. Drilled plug & cmt 326' to 352'. Started drlg ahead. Drld thru w/12-1/2 hole to 2978'. Reduced to 8-1/2" hole, drld to 4030'.
5-5-79
- 5-6-79 C&CM. PU core bit & bbl. WIH. Cut core #1 from 4035'-4095', Core #2 from 4095-4155', Core #3 from 4155-4215', Core #4 from 4215-75', Core #5 from 4275-4335', Core #6 from 4335-4395', Core #7 from 4395-4442', Core #8 from 4442-4485', Core #9 from 4485-4545', Core #10 from 4545-4605', Core #11 from 4605-4665', Core #12 from 4665-4725', Core #13 from 4725-4785', Core #14 from 4785-4845', Core #15 from 4845-4900'.
- 5-19-79 Circ & cond mud. RU to log.
- 5-20-79 Logged FDC-CNL & DHC Sonic - GR - Cal.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED  W.J. Mueller TITLE Senior Engineering Specialist DATE 5-25-79

APPROVED BY  Jerry Sexton TITLE DATE MAY 31 1979

CONDITIONS OF APPROVAL, IF ANY: Dist 1, Supv.

RECEIVED

MAY 31 1979

OIL CONSERVATION COMM.
HOBBS, N. M.