

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

API No. 30-025-26230

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
B-1576	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REPER OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - 10 (FORM C-103) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER		7. Unit Agreement Name	
2. Name of Operator		East Vacuum Grayburg-San Andres Unit	
3. Address of Operator		8. Name of Lease Owner	
Phillips Petroleum Company		East Vacuum Grayburg-San Andres Tract 3229	
4. Address of Operator		9. Well No.	
Room 401, 4001 Penbrook Street, Odessa, Texas 79762		005	
4. Location of Well		10. Field and Pool, or Well Unit	
UNIT LETTER <u>M</u> <u>1110</u> FEET FROM THE <u>South</u> LINE AND <u>1290</u> FEET FROM		Vacuum Grayburg/San Andre	
THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>17-S</u> RANGE <u>35-E</u> N.M.P.M.			
11. Elevation (Show whether DF, RT, GR, etc.)		12. County	
3965' GR		Lea	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	
		OTHER <u>Total Depth</u> ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-21-79 Ran 7" csg to 4877' w/Rts Packer @ 3030' & DV Tool @ 2977'.
Cmt w/350 sxs Class H w/1/4# Flocele for first stage. Displaced first stage. Set Rts & opened DV tool. Cmt w/1750 sxs Trinity LW w/12# salt, 10% Dia-D, 1/4# Flocele & 3# Gilsonite per sx @ 11.3 ppg. Tail in w/100 sxs Class H w/8# salt @ 15.9 ppg. Displaced w/700 psi & bumped plug 2200 psi. Circ 395 sxs TLW cmt & 40 sxs Class H cmt to surface. WOC ND BOP's & cut 7" csg & 13-3/8" csg & Head. Job complete @ 12:00 midnight. Released rig. Prep to perforate and test.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed W.J. Mueller TITLE Senior Engineering Specialist DATE 5-25-79

APPROVED BY Jerry Sexton TITLE Dist 1, Supv. DATE MAY 31 1979

RECEIVED

MAY 31 1979

OIL CONSERVATION COMM.
HOBBS, N. M.