

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-101
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

API NO. 30-025-26378

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
B-1482-3	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO CEASE OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Phillips Petroleum Company		East Vacuum Gb/San
3. Address of Operator		Andres Unit, Tract 2720
Room 401, 4001 Penbrook St., Odessa, TX 79762		9. Well No.
4. Location of Well		005
UNIT LETTER B, 1630 FEET FROM THE East LINE AND 1215 FEET FROM		10. Field and Pool, or Wildcat
THE North LINE, SECTION 27 TOWNSHIP 17-S RANGE 35-E N.M.P.M.		Vacuum Gb/San Andres
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3937 GR		Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	
		OTHER Total depth ☒	

17. Descriptive Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-14-79 MI D&B Drlg. Spudded w/17-1/2" hole @ 2:00 P.M. 8-14-79. Ran 11 jts 13-3/8" 54.5# K-55 8RD ST&C csg. Set @ 367'. Cmtd w/675 sx Cl H and 2% CaCl₂ and 1/4#/sx Flocele. Circ 300 sx cmt. WOC 20 hrs.

8-15-79 Tested BOP's O.K. Drld w/12-1/4" drld cmt, plug, shoe and 20'. Drld ahead 8-3/4" hole to 4900 TD reached @ 8-29-79 Logging.

9-2-79 Ran 118 jts to 4895', 7" 23# K-55 ST&C csg. Cmt w/1350 sx TLW w/12# salt, 10% DD, 1/4# Flocele, 3# Gilsonite, followed by 345 sx Cl H w/8# salt. Circ 249 sx cmt. Csg set @ 4875'. Cut 7" csg 16 hrs after plugdown. Released rig. Perp. to perf.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. Mueller TITLE Senior Engineering Specialist DATE 9-10-79

Orig. Signed By
Jerry Sexton

APPROVED BY Dist. 1. Supv. TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

SEP 14 1979