

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API NO. 30-025-26380

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

B-1839-1

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
(SEE APPLICATION FOR PERMIT TO DRILL OR TO DEEPEN FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
Phillips Petroleum Company

3. Address of Operator
Room 401, 4001 Penbrook, Odessa, TX 79762

4. Location of Well
UNIT LETTER E 2570 FEET FROM THE North LINE AND 1110 FEET FROM

THE West LINE, SECTION 27 TOWNSHIP 17-S RANGE 35-E NADP.

10. Field and Pool or Anticline
Vacuum Gb/SA

11. Elevation (Show whether DF, RT, GR, etc.)
3934 GR

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	
		OTHER Total depth ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work; SEE RULE 1105.)

8-26-79 MI Marc Drlg. Spudded w/17-1/2" @ 2:00 A.M. 8-26-79. Ran 385' of 13-3/8", 48# H-40 csg.

8-27-79 Cmt 13-3/8" csg w/675 sx Cl H w/2% CaCl₂, w/1/4#/sx Flocele in 1st 150 sx. Csg set @ 372', 290 sx back to surface. WOC 18 hrs, cut 13-3/8" csg. Tested BOP's OK. Drld w/12-1/4" bit cmt and 20' formation.


8-29-79 Drld ahead w/7-7/8" bit.


9-9-79 Reached TD 4800'. RU to Log.

9-11-79 Ran 124 jts of 5-1/2", 14# K-55, 8 rd ST&C csg. Set at 4799'. Cntd w/900 sxs TLW w/12#/sx salt, 10% DD, 1/4#/sx Celloflake and 3#/sx Gilsonite, followed w/450 sxs Cl H w/8#/sx salt. Circ 35 sxs cmt. WOC 18 hrs.

9-12-79 Cut 5-1/2" csg. Released rig.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED  W. J. Mueller TITLE Senior Engineering Specialist DATE 9-13-79

APPROVED BY  Jerry Sexton TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: SEP 20 1979