

| | |
|------------------------|--|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| DATE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

API No. 30-025-26383

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
SEE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Phillips Petroleum Company

Address of Operator

Room 401, 4001 Penbrook Street, Odessa, Texas 79762

Location of Well

UNIT TESTED I 2630 FEET FROM THE South LINE AND 1330 FEET FROM

THE East LINE, SECTION 28 TOWNSHIP 17-S RANGE 35-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)

DF 3943.3

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

A-1320

7. Unit Agreement Name East Vacuum Gb/San Andres Unit

8. Farm or Lease Name East Vacuum Gb/San Andres Unit, Tract 2801

9. Well No.

006

10. Field and Pool, or Wildcat

Vacuum Gb/San Andres

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPS. ☒

CASING TEST AND CEMENT JOB ☒

OTHER Total Depth ☒

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-25-79 MI Marc Drlg.

10-27-79 Spudded w/11" hole drld to 355'. Ran 8-5/8", 24#, K-55 csg set at 354'. Cmt w/300 sxs Class "H" w/2% CaCl₂ and 1/4# Flocele. Circ 50 sxs to surface. Temp of cmt 92°, zone temp 64°, estimated cmt strength 500+, cmt in place 15 hrs before testing.

10-28-79 Drld ahead with 7-7/8" hole.

11-6-79 Reached TD 4800'. Logging.

11-7-79 Ran 117 jts, 5-1/2", 14#, K-55 csg.

11-8-79 Cmt w/1100 sxs TLW, w/12# salt, 10% D.D., 1/4# Flocele, 3# Gilsonite. Tail in w/500 sxs Class "H" w/8# salt. Circ 100 sxs TLW to surface csg set at 4797'. Release rig.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller

TITLE Senior Engineering Specialist

DATE November 15, 1979

Original Signed by
Larry Sexton

Don L. Burt

APPROVED BY

TITLE

DATE

NOV 21 1979

CONDITIONS OF APPROVAL, IF ANY: