

NO. OF COPIES RECEIVED	
DISTRIBUTION	
ANTA FE	
ILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

API No. 30-025-26380

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
SEE MAPS AND LOCATION FOR PERMIT "M" FORM C-101 FOR SUCH PROPOSALS.

OIL WELL ☒	NATURAL GAS WELL ☐	OTHER ☐	5d. Indicate Type of Lease State ☒ Fee ☐
6. Name of Lessee Phillips Petroleum Company			5. State Oil & Gas Lease No. B-1399-10
7. Location of Well Room 401, 4001 Penbrook Street, Odessa, Texas 79762			7. Unit Agreement Name East Vacuum Gb/San Andres Unit
8. Location of Well UNIT LETTER 0, 1533 FEET FROM THE East LINE AND 130 FEET FROM T-2 South LINE, SECTION 29 TOWNSHIP 17-S RANGE 35-E			8. Name of Lease Name East Vacuum Gb/San Andres Unit, Tract
9. Elevation (Show whether DF, RT, GR, etc.) GL 3966.1 RKB 2975.7			9. Well No. 2913 008
10. Field and Pool, or Wildcat Vacuum Grayburg/San Andres			10. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
ILL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	
		OTHER Total depth ☐	

11. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-22-79 "H" Coral Drlg. Spudded 11" hole.

9-23-79 Drld to 351'. Ran 9 jts 352', 8-5/8", 24#, K-55, ST&C csg set @ 351' cmt w/250 sxs Cl "H" w/2% CaCl and 1/4#/sx Flocele. Circ 125 sxs. WOC 4 hrs, temp of cmt 70° - 80°, formation temp in zone 65°, cmt strength over 500 PSI, time cmt in place prior to starting test 14-1/2 hrs. Cut 8-5/8" csg NU BOP's, test OK.

10-5-79 Drld ahead 7-7/8" hole to 4800 T.D. Ran 125 jts 5-1/2" csg, 14#, K-55 set @ 4800'. Cmt w/1200 sxs TLW w/12 sxs Salt, 10% DD, 1/4# sx Flocele and 3# Gilsonite, followed w/400 sxs Cl "H" w/8# salt. Circ 100 sxs cmt @ surface. Displ plug w/20 bbls acetic acid and 96 bbls fresh wtr. WOC 3 hrs. Cut 5-1/2" and 8-5/8" csg. Job complete, released rig 12:00 A.M., 10-7-79. Prep to perf and complete.

12. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed W. J. Mueller TITLE Senior Engineering Specialist DATE October 15, 1979

Orig. Signed by
Jerry Sexton
Dist 1, Supr.

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: