


DOUBLE PREVENTER OPTION



- ① SERIES 900 RAM-TYPE BOP
- ② 12" SERIES 900 VALVE
- ③ SERIES 900 DRILLING SPOOL
- ④ 12" ID PRESSURE GAUGE
- ⑤ 12" SERIES 900 CHOKER
- ⑥ 12" SERIES 900 CHECK VALVE
- ⑦ 12" SERIES 900 STEEL TEE

NOTES:

1. 3000 PSI WP CLAMP
PLUGS MAY BE SUBSTITUTED
FOR FLANGES

2. VALVES MAY BE EITHER HAND OR POWER
OPERATED BUT, IF POWER OPERATED,
THE VALVES FLANGED TO THE BOP RUN
MUST BE CAPABLE OF BEING OPENED AND
CLOSED MANUALLY OR CLOSE ON POWER
FAILURE AND BE CAPABLE OF BEING
OPENED MANUALLY

..... OPTIONAL EQUIPMENT

PHILLIPS PETROLEUM COMPANY

3000 PSI WORKING PRESSURE
BLOWOUT PREVENTER HOOK-UP
(SERIES 900 FLANGES OR BETTER)

REV 6/73

FIGURE NO. 7

RECEIVED

JUL 10 1973

O.C.D., HOBBS, OFFICE

