

UNIT STATES OF AMERICA
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
MEXICO 88240

Subject Bureau No. 100-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ <u>DXA</u>	5. LEASE DESIGNATION AND SERIAL NO. <u>LC-064790</u>
2. NAME OF OPERATOR <u>AMOCO PRODUCTION COMPANY</u>	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR <u>P.O. BOX 68 HOBBS, NEW MEXICO 88240</u>	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <u>660' FNL x 1980' FEL</u> <u>(UNIT B, NW14, NE14)</u>	8. FARM OR LEASE NAME <u>Federal "AC"</u>
14. PERMIT NO. <u>3002526469</u>	9. WELL NO. <u>1</u>
15. ELEVATIONS (Show whether DE, RT, GR, etc.) <u>3644.3' GR</u>	10. FIELD AND POOL, OR WILDCAT <u>Buffalo Penn</u>
	11. SEC. T. R. M. OR BLK. AND SURVEY OR AREA <u>18-19-33</u>
	12. COUNTY OR PARTIAL <u>Lea</u>
	13. STATE <u>NM</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1154 9-19-85. Killed well and POH with tubing. Ran CIBP and set at 12,210'. Displaced hole with brine gel. Placed the following plugs:

Interval	Type Cement	SX
12,210-12,010'	Class H	25
9,600-9,400'	Class H	25
7,100'-6,900'	Class H	25
5,125-4,925'	Class H	25
3,000-2,800'	Class H	25
1,500-1,300'	Class H	25
555-355'	Class H	25

0 + 5 BLM, 1 JRB, 1 - FJN, 1 - CMH

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Administrative Analyst (SG)

DATE

9-27-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

1-16-86

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Interval

* 60'-0'

Type Cement

Class H

Sx

25

* Perforated 60'-61' and circulated inside and outside 5 1/2" casing.

Cut-off well head and installed PxA marker. M054 9/25/85.

RECEIVED

JAN 24 1986

HOBBS OFFICE