

RECOMMENDED PROCEDURE
EAST VACUUM GB/SA UNIT
TRACT 3202-009

1. MIRU DD WSU. KILL WELL IF NECESSARY. RIG-UP BOP. COOH W/ 2-7/8" INJECTION TBG & BAKER LOK-SET PKR.
- NOTE: SCANALOG TBG AS PULLED.
2. RIH W/ SANDLINE PUMP AND TAG FILL. CLEAN OUT IF POSSIBLE W/ SANDLINE PUMP TO +/- 4700'. IF UNABLE TO CLEAN OUT, COOH W/ SANDLINE PUMP. IF FILL IS SOFT AND EASILY RECOVERABLE, RIH W/ HYDRO-STATIC BAILER AND CLEAN OUT TO 4700'. IF FILL IS HARD & WELL PACKED, MIRU REVERSING UNIT. RIH W/ 4-7/8" BIT, COLLARS & 2-7/8" J-55 WORKSTRING TBG. CLEAN OUT TO 4700'.
3. RIH W/ OPEN ENDED 2-7/8" J-55 WORKSTRING TBG TO +/- 4690'. SPOT 50 SKS CLASS C NEAT CMT INTO THE RAT HOLE. SPOT W/ PRODUCED BRINE. PULL TBG TO 4200' AND WASH UP. LOWER TBG IN ONE OR TWO JOINT LENGTHS AND REVERSE HOLE AS GOING IN. RUN TBG TO +/- 4630'. CIRCULATE HOLE. COOH W/ TBG. S-D FOR AT LEAST 24 HOURS.
4. RIH W/ 4-7/8" BIT, COLLARS AND 2-7/8" WORKSTRING TBG. TAG TOC AND DRILL OUT TO 4650' AS NECESSARY. COOH W/ TBG AND TOOLS.
5. MIRU HLS. RU LUBRICATOR AND TEST TO 1000#. RUN GR-COLLAR LOG FROM 4650' TO 4000' (USE WELEX DUAL LATERLOG MICRO-SFL FOR DEPTH CONTROL). USING THE HLS GR-COLLAR LOG FOR DEPTH CONTROL, PERFORATE THE FOLLOWING ZONES W/ 23 GRAM CHARGES (4" GUNS):

RUN 1	4634-42'	8'	2 SPF	17 HOLES
	4610-24'	14'	2 SPF	29 HOLES
RUN 2	4588-4604'	16'	2 SPF	33 HOLES
	4572-76'	4'	2 SPF	9 HOLES
RUN 3	4561-65'	4'	2 SPF	9 HOLES
	4550-58'	8'	2 SPF	17 HOLES
RUN 4	4536-47'	11'	2 SPF	23 HOLES
	4531-34'	3'	2 SPF	7 HOLES
RUN 6	4498-4520'	22'	2 SPF	45 HOLES
RUN 7	4478-94'	16'	2 SPF	33 HOLES
RUN 8	4462-76'	14'	2 SPF	29 HOLES
	4456-59'	3'	2 SPF	7 HOLES
RUN 9	4444-46'	2'	2 SPF	5 HOLES
	4428-39'	11'	2 SPF	23 HOLES
RUN 10	4414-25'	11'	2 SPF	23 HOLES
	4409-12'	3'	2 SPF	7 HOLES
RUN 11	4395-4406'	11'	2 SPF	23 HOLES
	4386-94'	8'	2 SPF	17 HOLES
		169'		356 HOLES

RD LUBRICATOR. RDMO HLS.

RECEIVED

JUL 28 1991

677
HONOLULU