

DISTRICT I
P.O. Box 1980, Hobbs NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-26522
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	B-2519
7. Lease Name or Unit Agreement Name	EAST VACUUM GB/SA UNIT TRACT 3467
8. Well No.	001
9. Pool name or Wildcat	VACUUM GRAYBURG/SAN ANDRES

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	2. Name of Operator Phillips Petroleum Company
3. Address of Operator 4001 Penbrook Street, Odessa, TX 79762	4. Well Location Unit Letter B : 1050 Feet From The NORTH Line and 1520 Feet From The EAST Line Section 34 Township 17-S Range 35-E NMPM LEA County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3929' GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. THIS IS AN NMCD RULE 118 WELL.
2. NOTIFY THE NMCD HOBBS OFFICE 24 HOURS PRIOR TO P&A OPERATIONS.
3. MIRU SIERRA WELL SERVICE, CIRC WELL W/10 PPG BRINE, NU BOPE, COOH W/2-7/8" TBG, GIH & ATTEMPT TO CLEAN OUT TO 4,400', CIRC 5-1/2" CSG W/9.5 PPG MUD-LADEN FLUID.
4. NOTE: ALL CEMENT PLUGS, CLASS "C", MIXED AT 14.8 PPG.
5. SPOT PLUG NO. 1, 60 SXS CEMENT, 4,400'-4,000', COVERS THE SAN ANDRES & GRAYBURG, PULL UP HOLE TO 3,000, REVERSE OUT, WOC & TAG.
6. SPOT PLUG NO. 2, 75 SXS CEMENT, 2,941'-2,400', COVERS THE YATES & BAD CSG 2,800'-2,500', PULL UP HOLE TO 1,700', REVERSE OUT, PRESSURE TEST 5-1/2" CSG TO 500 PSI, SDON.
7. TAG PLUG NO. 2, SPOT PLUG NO. 3, 25 SXS CEMENT, 1,700'-1,600', COVERS THE SALT TOP.
8. SPOT PLUG NO. 4, 50 SXS CEMENT, 420'-3', CUT OFF CSG, INSTALL MONUMENT MARKER, PREFORM RECLAMATION WORK>

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. M. Sanders TITLE SR. REGULATION ANALYST DATE 04/01/96

TYPE OR PRINT NAME L. M. SANDERS

TELEPHONE NO. 915/368-1488

(This space for State Use)

APPROVED BY TITLE DATE APR 4 1996
CONDITIONS OF APPROVAL, IF ANY: