

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

IL CONSERVATION DIVISIC
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L - 5316
7. Unit Agreement Name
8. Farm or Lease Name Shearn West
9. Well No. 1
10. Field and Pool, or Unitcat S. Shoe Bar (Morrow)
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry
2. Name of Operator Sol West III
3. Address of Operator P. O. Box 10151, El Paso, Texas 79992
4. Location of Well UNIT LETTER J, 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 3 TOWNSHIP 17-S RANGE 35-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3959.7' GL; 3975.7' KB

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plugs were set on May 6, 1980 in the subject well as follows:

- (1) 5 1/2" CIBP set at 12,840' with 10 sack (35') cement.
- (2) 5 1/2" CIBP set at 12,280' with 10 sack (35') cement.
- (3) 5 1/2" CIBP set at 10,060' with 10 sack (35') cement.
- (4) 35 sack plug (150') set from 7955'-8130' KB.
- (5) 70 sack plug (240') set from 4730'-4970' KB.
- (6) 45 sack plug (150') set from 1912'-2062' KB.
- (7) 10 sack plug (35') at surface.

Welded on historical marker. Fenced reserve pits. Pits will be filled and the location will be leveled and cleared of junk. 4907' of casing was left in the hole. Plugging procedure was discussed with the district office prior to proceeding.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Agent DATE June 19, 1980
APPROVED BY [Signature] TITLE DATE JAN 1981
CONDITIONS OF APPROVAL, IF ANY: