

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
L-5316

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT L-1" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Sol West III	8. Farm or Lease Name Shearn West
3. Address of Operator P. O. Box 10151, El Paso, Texas 79992	9. Well No. 1
4. Location of Well UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 3 TOWNSHIP 17-S RANGE 35-E N.M.P.M.	10. Field and Pool, or Wildcat So. Shoe Bar (Morrow)
15. Elevation (Show whether DF, RT, GR, etc.) 3,659.7' GL 3,675.7' KB	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER Progress Report (Drilling) ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1-12-80: At 3115' drilling in anhydrite and salt. Made 960'. Totco at 2382' was 1°; at 2890' was 1°. Mud wt. = 9.7#. Viscosity = 34.
- 1-13-80: At 3518' drilling in anhydrite and gyp. Made 403'. Totco at 3390' was 1°; at 3487' was 3/4°. Mud wt. = 10.1#. Viscosity = 34. Chlorides = 176,000. Oil = 2%.
- 1-14-80: At 3860' drilling in anhydrite, gyp and lime. Made 342'. Mud wt. = 10.2#. Viscosity = 34. Chlorides = 176,000. Changed bit.
- 1-15-80: At 4156' drilling in lime. Made 296'. Totco at 3990' was 1 1/4°. Mud wt. = 10.1#. Viscosity = 34.
- 1-16-80: At 4400' drilling in lime. Made 244'. Mud wt. = 10.4#. Viscosity = 34. Chlorides = 193,000.
- 1-17-80: At 4600' drilling in lime. Made 200'. Totco at 4415' was 1/2°. Mud wt. = 10.4#. Viscosity = 35. Chlorides = 190,000. Unplugged jets.
- 1-18-80: At 4777' drilling in lime. Made 177'. Mud wt. = 10.4#. Viscosity = 34. Chlorides = 193,000. Changed bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Patty Robbins TITLE Agent

DATE 1-18-80

Orig. Signed by

Jerry Sexton

Dist. L. Supv.

APPROVED BY

TITLE

DATE

JAN 21 1980

CONDITIONS OF APPROVAL, IF ANY: