

(Grayburg-San Andres) Perfs 4441-4502'; WATER INJECTION WELL

F.R. 11-19-79
(Grayburg-San Andres)
4-19-80 AMEND WELL NUMBER: Formerly reported as #5
11-30-79 Drlg 1619'
12-12-79 TD 4689'; Trip
Cored (Grayburg-San Andres) 4390-4450', rec 60',
no descr
Cored (Grayburg-San Andres) 4450-4510', rec 60',
no descr
Cored (Grayburg-San Andres) 4510-69', rec 59',
no descr
Cored (Grayburg-San Andres) 4569-4618', rec 49',
no descr
Cored (Grayburg-San Andres) 4618-89', rec 71',
no descr
4-14-80 TD 4800'; PBD 4750'; Complete
Perf (Grayburg-San Andres) 4441-45', 4447-56',
4460-64', 4487-4537', 4542-45', 4461-68',
4-3-9 NM

LEA

Vacuum

NM

PHILLIPS PETROLEUM CO. WI-5 East Vacuum
(Grayburg-San Andres)
Unit Tr. 2717
Sec 27, T17S, R35E

Page 2

4-14-80

Continued

4475-86', 4590-4602'

Acid (4441-4602') 12,000 gals (15%)

LOG TOPS: Rustler 1617', Yates 2902',

Queen 3747', Grayburg 4100', San Andres 4400'

4-19-80

COMPLETION ISSUED

4-3-9 NM

IC 30-025-70456-79