

NO. OF COPIES RECEIVED		
DISTRIBUTION		
CANYA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-85

API No. 30-025-26568

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Phillips Petroleum Company

Address of Operator

Room 401, 4001 Penbrook Street, Odessa, Texas 79762

Location of Well

UNIT LETTER J 1330 FEET FROM THE East LINE AND 2630 FEET FROM

THE South LINE, SECTION 19 TOWNSHIP 17-S RANGE 35-E N.M.P.M.

15. Elevation (Show whether DF, RT, CR, etc.)

3986.0 GR

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

B-1398

7. Unit Agreement Name East

Vacuum Gb/SA Unit

8. Farm or Lease Name East Vacuum

Gb/SA Unit, Tract 1910

9. Well No.

003

10. Field and Pool, or Wildcat

Vacuum Gb/SA

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☒

OTHER Total depth ☒

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1-30-80 MI Cactus Drlg. Spud in 1-30-80 w/12-1/4" bit. Ran 9 jts 8-5/8" 24# K-55 ST&C csg set @ 357'. Cmt w/350 sxs Cl "H" w/5% CaCl and 1/4# Flocele. Bumped Plug. Circ 88 sxs cmt to surface. Temp cmt 60°, zone temp 63°, strength of cmt 2400 PSI. Cmt in place 11 hours before testing. Tested BOP's and csg. O. K.
- 2-11-80 Reached 4900' TD. Running logs.
- 2-13-80 Ran 118 jts 4-1/2" 36# N-80 csg set @ 4900'. Cmt w/1200 sxs TLW w/10% DD and 12# sx salt + 1/4#/sx Flocele + 3#/sx Gilsonite + 400 sxs ClH w/5#/sx salt. Circ 254 sxs to surface. Release rig 2-13-80. Prep to perf.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

W. J. Mueller, TITLE Senior Engineering Specialist DATE February 29, 1980

Orig. Signed By

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: